Tintometer[®] Group Water Testing



phone: +49 231 94510-0

phone: +44 1980 664800

e-mail: SDS@tintometer.com

e-mail: sales@tintometer.de

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2023 Version number 5 (replaces version 4) Revision: 15.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Product name: Reference Standard Saybolt Colour +12
- · Catalog number: 134060
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation: Coloured Standard Solution for calibration purposes
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Tintometer GmbH Schleefstraße 8-12 44287 Dortmund www.lovibond.com

The Tintometer Limited Lovibond® House Sun Rise Way Amesbury Wiltshire SP4 7GR United Kingdom Made in UK

· Informing department: e-mail: sds@lovibond.com Product Safety Department

· 1.4 Emergency telephone number:

+44 1235 239670 Languages: English

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS07

GHS08

· Signal word Danger

Printing date 15.11.2023 Version number 5 (replaces version 4) Revision: 15.11.2023

Product name: Reference Standard Saybolt Colour +12

(Contd. of page 1)

· Hazard-determining components of labelling:

Kerosine: distillates, hydrotreated light

(D94/69 p1249) 4

Hazard statements

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P280 Wear protective gloves.

P264 Wash contaminated body parts thoroughly after handling.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container to an approved waste disposal plant.

· 2.3 Other hazards No further relevant information available.

· Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

Determination of endocrine-disrupting properties

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of organic compounds.

· Dangerous components:			
CAS: 64742-47-8	Kerosine : distillates, hydrotreated light	80-100%	
EINECS: 265-149-8	(D94/69 p1249) 4		
Index No: 649-422-00-2 Reg.nr.: 01-2119484819-18-XXXX	♦ Asp. Tox. 1, H304; ♦ Skin Irrit. 2, H315		
CAS: 1330-20-7	xylene, mixed isomers, pure	<0.1%	
EINECS: 215-535-7 Index No: 601-022-00-9	♠ Flam. Liq. 3, H226; ♠ Aquatic Acute 1, H400 (M=1); ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information

Personal protection for the First Aider!

Instantly remove any clothing soiled by the product.

· After inhalation

Supply fresh air or oxygen.

Call a doctor immediately.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact Rinse opened eye for several minutes (at least 15 min) under running water. Then consult doctor.

After swallowing

Rinse out mouth and then drink 1-2 glasses of water.

Do not induce vomiting: instantly call for medical help.

4.2 Most important symptoms and effects, both acute and delayed:

irritations

after swallowing and inhalation:

breathing difficulty

coughing

dizziness

gastric or intestinal trouble

Danger

Danger of pneumonia.

Danger of pulmonary oedema.

(Contd. on page 3)

Printing date 15.11.2023 Version number 5 (replaces version 4) Revision: 15.11.2023

Product name: Reference Standard Saybolt Colour +12

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

Use fire fighting measures that suit the environment.

Water, Carbon dioxide (CO₂), Foam, Fire-extinguishing powder

CO₂, extinguishing powder or water spray jet. Fight larger fire with alcohol-resistant foam.

For safety reasons unsuitable extinguishing agents

Water with a full water jet.

Large Fire: Use of water spray when fighting fire may be inefficient.

5.2 Special hazards arising from the substance or mixture

combustible

Formation of toxic gases is possible during heating or in case of fire.

Can be released in case of fire:

Carbon monoxide (CO) and carbon dioxide (CO2)

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Ensure adequate ventilation

· Advice for emergency responders: Protective equipment: see section 8

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

· Advice on safe handling:

Ensure good ventilation/exhaustion at the workplace.

Keep ignition sources away - Do not smoke.

Hygiene measures:

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Take off immediately all contaminated clothing.

Wash hands during breaks and at the end of the work.

Do not eat, drink or smoke when using this product.

· 7.2 Conditions for safe storage, including any incompatibilities

· Requirements to be met by storerooms and containers: Store in cool location.

Printing date 15.11.2023 Version number 5 (replaces version 4) Revision: 15.11.2023

Product name: Reference Standard Saybolt Colour +12

(Contd. of page 3)

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Protect from heat and direct sunlight.

Protect from the effects of light.

Protect from humidity and keep away from water.

- · Recommended storage temperature: 20°C +/- 5°C
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Recommended monitoring procedures:

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and DIN EN 689.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7

· Individual protection measures, such as personal protective equipment

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled.

· Eye/face protection

Safety glasses

Use safety glasses that have been tested and approved in accordance with government standards such as EN 166.

Hand protection

Protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

Penetration time of glove material

Value for the permeation: Level = 1 (< 10 min)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Other skin protection (body protection): Protective work clothing.
- · Breathing equipment: Use breathing protection against the effects of fumes/dust/aerosol.
- · Recommended filter device for short term use: Filter A
- · Environmental exposure controls Do not allow product to reach sewage system or water bodies.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state
Form:
Colour:
Odour:
Odour threshold:
Fluid
Liquid
Light brown
Characteristic
Not determined.

· Melting point/Freezing point: -60°

Boiling point or initial boiling point and boiling range 192–256°C (CAS: 64742-47-8 Kerosine : distillates, hydrotreated light

(D94/69 p1249) 4)

· Flammability combustible

• Explosive properties: Product is not explosive. However, formation of explosive air/steam

mixtures is possible.

(Contd. on page 5)

Printing date 15.11.2023 Version number 5 (replaces version 4) Revision: 15.11.2023

Product name: Reference Standard Saybolt Colour +12

(Contd. of page 4)

· Lower and upper explosion limit	
Lower:	0.5 Vol % (CAS: 64742-47-8 Kerosine : distillates, hydrotreated light (D94/69 p1249) 4)
Upper:	6.5 Vol % (CAŚ: 64742-47-8 Kerosine : distillates, hydrotreated light (D94/69 p1249) 4)
· Flash point:	77°C (CAS: 64742-47-8 Kerosine : distillates, hydrotreated light (D94/69 p1249) 4)
· Auto-ignition temperature:	225°C (CAS: 64742-47-8 Kerosine : distillates, hydrotreated light (D94/69 p1249) 4)
Decomposition temperature:	Not determined.
pH	Mixture is non-soluble (in water).
Kinematic viscosity at 40°C	<20.5 mm²/s
Solubility	
Water:	Not miscible or difficult to mix
· Partition coefficient n-octanol/water (log value)	Not applicable (mixture).
· Vapour pressure:	Not determined.
· Density and/or relative density	
Density at 20°C:	>0.62-<0.97 g/cm³
· Relative density:	Not determined.
· Relative gas density	Not determined.
Particle characteristics	Not applicable (liquid).
· 9.2 Other information	
Information with regard to physical hazard classes	
· Corrosive to metals	Void
Other safety characteristics	
Oxidising properties:	none
Additional information	
· Solids content:	0 %
· Solvent content:	
· Organic solvents:	<0.1 %

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Fumes can combine with air to form an explosive mixture.
- · 10.2 Chemical stability Stable at ambient temperature (room temperature).
- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents
- · 10.4 Conditions to avoid Strong heating (decomposition)
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: see section 5

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:		
CAS: 64742-47-8 Kerosine : distillates, hydrotreated light (D94/69 p1249) 4		
Oral	LD50	>5000 mg/kg (rat) (IUCLID)
Dermal	LD50.	>2000 mg/kg (rabbit) (IUCLID)
Inhalative	LC50	>5.28 mg/l /4h (rat) (ECHA: vapour; no test animals died during exposure or the post-exposure observation period.)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 15.11.2023 Version number 5 (replaces version 4) Revision: 15.11.2023

Product name: Reference Standard Saybolt Colour +12

(Contd. of page 5)

· Information on components:		
CAS: 64742-47-8 Kerosine : distillates, hydrotreated light (D94/69 p1249) 4		
Irritation of skin		(rabbit: irritation) ECHA: migrated information: read-across based on grouping of substances (category approach)
Irritation of eyes		(rabbit: no irritation) ECHA: migrated information: read-across based on grouping of substances (category approach)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · Additional toxicological information:

CAS: 64742-47-8 Kerosine : distillates, hydrotreated light (D94/69 p1249) 4

. (source: GESTIS)

Main toxic effects of Petroleum in analogy:

acute: degreasing and irritating effect on the skin,

Lung damage when inhaling highly concentrated aerosols (aspiration). Depression of the central nervous system, gastrointestinal complaints and renal dysfunction after massive oral intake

chronic: skin changes

After inhalation/oral uptake of high doses, the systemic effects set in quickly: headache, dizziness, euphoria, followed by drunkenness, accelerated pulse, tremor, cyanosis, spasms, deep anaesthesia, lack of reflexes -> circulatory failure and respiratory paralysis. Recovery in the course of the symptom sequence with a timely stop of exposure.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- Other information

Other dangerous properties can not be excluded.

According to the information available to us, the chemical, physical and toxicological properties of the substances mentioned in Chapter 3 have not been thoroughly investigated.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects Avoid transfer into the environment.
- · Water hazard:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to disposers of hazardous waste.

(Contd. on page 7)

Printing date 15.11.2023 Version number 5 (replaces version 4) Revision: 15.11.2023

Product name: Reference Standard Saybolt Colour +12

(Contd. of page 6)

European waste catalogue

16 05 08* discarded organic chemicals consisting of or containing hazardous substances

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

SECI	ION 14:	Transport	information

· 14.1 UN number or ID number · ADR, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMG instruments	O Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act UK
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Regulation (EU) 2019/1148 on the marketing and use of explosives precursors not regulated
- · Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (PIC)

None of the ingredients is listed.

· Regulation (EC) No 1334/2000 setting up a Community regime for the control of exports of dual-use items and technology:

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer:

None of the ingredients is listed.

· REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)

None of the ingredients is listed.

(Contd. on page 8)

Printing date 15.11.2023 Version number 5 (replaces version 4) Revision: 15.11.2023

Product name: Reference Standard Saybolt Colour +12

(Contd. of page 7)

· LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV)

None of the ingredients is listed.

Substances of very high concern (SVHC) according to REACH, Article 57

This product does not contain any substances of very high concern above the legal concentration limit of ≥ 0.1% (w / w).

· Substances of very high concern (SVHC) according to UK REACH

This product does not contain any substances of very high concern above the legal concentration limit of ≥ 0.1% (w / w).

- · Directive 2012/18/EU (SEVESO III):
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Information about limitation of use: Not required.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- · Training hints Provide adequate information, instruction and training for operators.
- Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

Abbreviations and acronyms:

OECD: Organisation for Economic Co-operation and Development

STOT: specific target organ toxicity

SE: single exposure

RE: repeated exposure

EC50: half maximal effective concentration

IC50: half maximal inhibitory concentration

NOEL or NOEC: No Observed Effect Level or Concentration

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of

Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Data arise from safety data sheets, reference works and literature.

IUCLID (International Uniform Chemical Information Database)

ECHA: European CHemicals Agency http://echa.europa.eu

GESTIS- Stoffdatenbank (Substance Database, Germany)

* Data compared to the previous version altered.