Lovibond® Colour Measurement Tintometer® Group



RT650 (diffuse/8) Compact Spectrophotometer

Affordable Benchtop Spectrophotometer, Diffuse 8° Sphere



- Ideal for Small to Medium-Sized Manufacturers
- Rugged Construction with Minimum Footprint
- Unique Sample Holder for Previewing Sample Area
- Removable Sample Holder to Measure Large Samples

Part Number: 407000

Reliable and Accurate Compact Benchtop Spectrophotometer

This affordable benchtop spectrophotometer is ideal for small to medium-sized manufacturers looking to establish accurate colour measurement in the work process. This small footprint and rugged construction means you can use it practically anywhere for multiple applications.

Reduces Rework for Faster Time to Market and Lower Costs

Improving the colour quality in the lab and in manufacturing can significantly reduce the danger of having to rework your products to address the requirements expected from your customers.

Immediately Identifies Colour Variance

Using standard measurement methods, the RT 650 immediately identifies and deviations in colour and gloss to ensure accurate color readings or to qualify visual inspection (SPIN/SPEX).

Compliance with ASTM D523 and ISO 2813

The RT 650 produces correlated 60° gloss value for more accurate assessment of sample gloss in compliance with ASTM D523 and ISO 2813.

Inter-Instrument Agreement

This benchtop instrument provides data with the Lovibond® handheld spectrophotometers enabling you to easily share data across the operation.

Adaptable

The RT 650 has an unique sample holder for previewing sample area and an additional removable sample holder to measure large samples which enable you to get the best use from this one instrument.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Oil and Gas | Pharmaceutical Industry

Application

Chemicals | Coatings | Food and Beverage | Household Products | Medical and Clinical Products | Pharmaceuticals and Cosmetics | Plastics | Textiles

RT650 (diffuse/8) Compact Spectrophotometer

This entry-level benchtop spectrophotometer has been designed to give fast, precise and accurate colour measurement information on a range of products.

Technical Data

Applicable Standard	ASTM 313 ASTM D1925 ASTM E308
Colour Type	Opaque
Interfaces	USB
Measuring Geomet-	d/8°, DRS spectral engine, fixed aperture simultaneous SPIN/SPEX
Spectral Interval	10 nm - measured; 10nm - output
Measurement Range	0 tot 200 % reflectie
Measurement Time	Approx 2 seconds
Power Supply	AC Adapter Requirements 90 - 130 VAC or 100 - 240 VAC 50 - 60 MZ 15 W max
Lamp Life	Approx 500,000 measurements
Storage Temperature	-4 to 122°F (-20° to 50°C)

Short Term Repeata- bility	$0.05 \Delta E$ ab on white ceramic
Spectral Range	400 - 700 nm
Portability	Benchtop
Dimensions	190 x 220 x 264 mm

Delivery Scope

Sturdy Box Including

- Instrument
- Calibration box
- Universal power supply
- Instruction manual

Tintometer GmbH

Lovibond® Water Testing Schleefstraße 8-12 44287 Dortmund Tel.: +49 (0)231/94510-0 sales@lovibond.com www.lovibond.com Germany

Tintometer Brazil

Caixa Postal: 271 CEP: 13201-970 Jundiaí – SP Tel.: +55 (11) 3230-6410

sales@lovibond.us

www.lovibond.com.br Brazil

The Tintometer Limited

Lovibond House Sun Rise Way Amesbury, SP4 7GR Tel.: +44 (0)1980 664800 Fax: +44 (0)1980 625412 sales@lovibond.uk www.lovibond.com UK

Tintometer Inc.

6456 Parkland Drive Sarasota, FL 34243 Tel: 941.756.6410 Fax: 941.727.9654 sales@lovibond.us www.lovibond.us USA

Tintometer China 9F, SOHO II C.

No.9 Guanghualu, Chaoyang District, Beijing, 100020 Customer Care China Tel.: 4009021628 Tel.: +86 10 85251111 Ext. 330 Fax: +86 10 85251001 chinaoffice@tintometer.com www.lovibond.com

China

Tintometer India Pvt. Ltd.

www.lovibondwater.in

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor Sanathnagar Industrial Estate, Hyderabad, 500018 Telangana Tel: +91 (0) 40 23883300 Toll Free: 1 800 599 3891/ 3892 indiaoffice@lovibond.in

India

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard, Lebuh Nilam 2, Bandar Bukit Tinggi, Klang, 41200, Selangor D.E Tel.: +60 (0)3 3325 2285/6 Fax: +60 (0)3 3325 2287 lovibond.asia@tintometer.com www.lovibond.com Malaysia

Tintometer Spain

Postbox: 24047 08080 Barcelona Tel.: +34 661 606 770 sales@tintometer.es www.lovibond.com Spain

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies