Lovibond[®] Water Testing

Tintometer® Group



Reviewed on 04/23/2021

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 04/23/2021

1 Identification

- · Product identifier
- · Trade name: Hardness Y / N
- · Catalogue number: 00515361, 515360BT, 515361BT, 503541, 00515369BT, 4515360BT, 4515361BT, 00503541
- · Application of the substance / the mixture: Reagent for water analysis
- Manufacturer/Supplier: Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 USA phone: (941) 756-6410 fax: (941) 727-9654 www.lovibond.us Made in Germany
- · Emergency telephone number: + 1 866 928 0789 (English, French, Spanish)

2 Hazard(s) identification

- · Classification of the substance or mixture
- GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Hazard Communication Standard (HCS).
- · Hazard pictograms



- · Signal word Warning
- Hazard statements H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- Precautionary statements
- P280 Wear protective gloves/protective clothing/eye protection.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P302+P352 If on skin: Wash with plenty of water.
- P313 Get medical advice/attention.
- · Other hazards No further relevant information available.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of organic and inorganic compounds
- Composition and Information on Ingredients:
- Percent ranges are used due to the confidential product information.

CAS: 9004-34-6 cellulose EINECS: 232-674-9 RTECS: FJ5691460

90–100%

Printing date 04/23/2021

Reviewed on 04/23/2021

Trade name: Hardness Y / N

| | | () | Contd. of page 1) | |
|---|-------------------|---|-------------------|--|
| CAS: 1310-65-2 EINECS: 215-183-4 | lithium hydroxide | ♦ Acute Tox. 3, H301; ♦ Skin Corr. 1A, H314; Eye Dam. 1, H318 | 1–≤2.5% | |
| • Additional information: For the wording of the listed hazard phrases refer to section 16. | | | | |

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air and to be sure call for a doctor.
- · After skin contact:
- Immediately rinse with plenty of water.
- If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes (at least 15 min) under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink 1-2 glasses of water.

Seek medical treatment. • Most important symptoms and effects, both acute and delayed

irritations after inhalation: mucous membrane irritation coughing breathing difficulty after swallowing of large amounts: sickness vomiting cramps

· Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- Can burn in fire.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

- Nitrogen oxides (NOx)
- LiOx
- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Ambient fire may liberate hazardous vapours.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- · Advice for non-emergency personnel:
- Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- Keep away from ignition sources
- · Advice for emergency responders: Protective equipment: see section 8
- · Environmental precautions: Do not allow product to reach sewage system or any water course.

\cdot Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Pick up mechanically.

Reviewed on 04/23/2021

Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 04/23/2021

Trade name: Hardness Y / N

Dispose contaminated material as waste according to item 13. • **Reference to other sections** See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

· Advice on safe handling: Prevent formation of dust.

- Hygiene measures: Avoid contact with the eyes.
 Take off immediately all contaminated clothing.
 Wash hands before breaks and at the end of work.
 Do not eat, drink or smoke when using this product.
- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from oxidizing agents.

 Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. Protect from exposure to the light. Protect from humidity and water. This product is hygroscopic.
 Recommended storage temperature: 20°C +/- 5°C (approx. 68°F)

- Recommended storage temperature: 20 C +/- 5 C (applox. 66
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

| · Components with limit values that require monitoring at the workplace: | | | | |
|--|---|--|--|--|
| CAS: 9004-34-6 cellulose | | | | |
| PEL (USA) | Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction | | | |
| REL (USA) | Long-term value: 10* 5** mg/m³ *total dust **respirable fraction | | | |
| TLV (USA) | Long-term value: 10 mg/m ³ | | | |
| EL (Canada) | Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction | | | |
| EV (Canada) | Long-term value: 10 mg/m³ paper fibre, total dust | | | |
| CAS: 1310-65-2 lithium hydroxide | | | | |
| WEEL (USA) | Ceiling limit value: 1 mg/m ³ | | | |
| EL (Canada) | Ceiling limit value: 1 mg/m ³ | | | |
| EV (Canada) | Short-term value: 1 mg/m³ anyhydrous | | | |

· Additional information: The lists that were valid during the creation were used as basis.

· Engineering measures: No further data; see item 7.

· Personal protective equipment:

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled.

• Breathing equipment: Use respiratory protective device against the effects of fume/dust/aerosol.

• Recommended filter device for short term use: Filter P2

Protection of hands:

Protective gloves

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

(Contd. of page 2)

Printing date 04/23/2021

Trade name: Hardness Y / N

Reviewed on 04/23/2021

(Contd. of page 3)

• Penetration time of glove material Value for the permeation: Level \leq 1 (10 min) The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Tightly sealed goggles
- Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment: Do not allow product to reach sewage system or any water course.

9 Physical and chemical properties

| · Information on basic physical and chemical properties | | |
|--|--|--|
| · Appearance: | | |
| Form / Physical state: | Tablets | |
| · Color: | Beige | |
| · Odor: | Odorless | |
| Odor threshold: | Not applicable. | |
| pH-value (1.4 g/l) at 20°C (68°F): | 10.8 | |
| Melting point/freezing point: | Not determined. | |
| Initial boiling point and boiling range: | Not determined. | |
| · Flash point: | 260°C (500°F) (CAS: 9004-34-6 cellulose) | |
| Flammability (solid, gas): | The mixture is capable of catching fire or being set on fire. | |
| Ignition temperature: | 420°C (788°F) (CAS 9004-34-5) | |
| Decomposition temperature: | > 150°C (> 302°F) (CAS 9004-34-5) | |
| Auto-ignition temperature: | Product is not self-igniting. | |
| Danger of explosion: | As the product is supplied it is not capable of dust explosion; however enrichment | |
| | with fine dust causes risk of dust explosion. | |
| Flammability or explosive limits: | | |
| · Lower: | Not determined. | |
| · Upper: | Not applicable (solid). | |
| Oxidizing properties: | none | |
| · Vapor Pressure: | Not applicable. | |
| · Density: | Not determined. | |
| Relative density: | Not determined. | |
| Vapor density: | Not applicable. | |
| Evaporation rate: | Not applicable. | |
| · Solubility(ies) | | |
| · Water: | Slightly soluble. | |
| Partition coefficient (n-octanol/water): | Not applicable (mixture). | |
| · Viscosity: | | |
| · Kinematic: | Not applicable (solid). | |
| Other information | | |
| Solids content: | 100.0 % | |
| | | |

10 Stability and reactivity

• **Reactivity** Dust can combine with air to form an explosive mixture.

- Chemical stability Stable at ambient temperature (room temperature).
- Possibility of hazardous reactions Aqueous solution reacts with metals. Aqueous solution reacts alkaline. Corrodes aluminium and zinc.
 Conditions to avoid strong heating Exposure to moisture.
 Incompatible materials:
- organic substances aluminum zinc

Printing date 04/23/2021

Trade name: Hardness Y / N

· Hazardous decomposition products: see section 5

11 Toxicological information

· Information on toxicological effects

· Acute toxicity: Based on available data, the classification criteria are not met.

| · LD/LC5 | · LD/LC50 values that are relevant for classification: | | | |
|---|--|-------------------|-------------------------|--|
| CAS: 9004-34-6 cellulose | | | | |
| Oral | LD50. | >5000 mg/kg (rat) | | |
| Dermal | LD50. | >2000 mg/kg | (rabbit) | |
| | | (RTECS, limi | , | |
| | | 2 lithium hyd | | |
| Oral | | | at) | |
| | | (RTECS) | | |
| · Primary | r irritan | t effect: | | |
| · on the s | skin: C | auses skin irri | ation. | |
| · on the e | eye: Ca | uses serious (| eye irritation. | |
| · Informa | tion or | n components | 3: | |
| CAS: 9004-34-6 cellulose | | | | |
| Irritation of skin OECD 404 (rabbit: no irritation) | | | | |
| Irritation | of eye | s OECD 405 | (rabbit: no irritation) | |
| · Sensitiz | ation: | No sensitizing | effects known. | |
| · Informa | tion or | n components | 3: | |
| CAS: 9004-34-6 cellulose | | | | |
| Sensitization OECD 406 (guinea pig: negative) | | | | |
| · Carcinogenic categories | | | | |
| · IARC (International Agency for Research on Cancer) | | | | |
| None of the ingredients is listed. | | | | |
| · NTP (National Toxicology Program) | | | | |
| None of the ingredients is listed. | | | | |
| · OSHA-Ca (Occupational Safety & Health Administration) | | | | |
| None of | None of the ingredients is listed. | | | |

· Other information: se

Synergistic Products

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction): The following statements refer to the mixture:

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

• STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met. · STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

· Additional toxicological information:

The following applies to lithium compounds in general:

after absorption: CNS disorders, ataxia (impaired locomotor coordination) due to disturbed electrolyte balance Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

(Contd. on page 6) US

Reviewed on 04/23/2021

| lose | | |
|-----------|-------------------------------|--|
| D 404 | (rabbit: no irritation) | |
| D 405 | (rabbit: no irritation) | |
| sitizing | geffects known. | |
| onent | S: | |
| lose | | |
| 06 (g | uinea pig: negative) | |
| ries | | |
| gency | for Research on Cancer) | |
| s is list | ed. | |
| ology P | Program) | |
| s is list | ed. | |
| nal Sa | fety & Health Administration) | |
| s is list | ed. | |
| e sect | ion 8 / 15 | |
| : None | | |
| | | |

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 04/23/2021

Trade name: Hardness Y / N

Reviewed on 04/23/2021

· Other information:

The following applies for lithium compounds in general: fish toxic from 100 mg/l, Daphnia toxic from 16 mg/l, plants toxic from 0,2 mg/l

- Persistence and degradability No further relevant information available.
- \cdot Bioaccumulative potential No further relevant information available.
- \cdot Mobility in soil No further relevant information available.
- Other adverse effects Avoid transfer into the environment.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information · UN-Number · DOT, IMDG, IATA none · UN proper shipping name · DOT, IMDG, IATA none Transport hazard class(es) · DOT, IMDG, IATA · Class none · Packing group · DOT, IMDG, IATA none · Environmental hazards: · Marine pollutant: No · Special precautions for user Not applicable. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: Not dangerous according to the above specifications.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara
Section 355 (Extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

Chemicals known to cause cancer:
None of the ingredients is listed.

(Contd. on page 7)

Reviewed on 04/23/2021

Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 04/23/2021

Trade name: Hardness Y / N

| | (Contd. of page 6 |
|--|-------------------|
| · Chemicals known to cause reproductive toxicity for females: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause developmental toxicity: | |
| None of the ingredients is listed. | |
| · New Jersey Right-to-Know List: | |
| CAS: 9004-34-6 cellulose | |
| · New Jersey Special Hazardous Substance List: | |
| None of the ingredients is listed. | |
| · Pennsylvania Right-to-Know List: | |
| CAS: 9004-34-6 cellulose | |
| · Pennsylvania Special Hazardous Substance List: | |
| None of the ingredients is listed. | |
| · EPA (Environmental Protection Agency) | |
| None of the ingredients is listed. | |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | |
| None of the ingredients is listed. | |

· Information about limitation of use: Not required.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

· Date of preparation / last revision 04/23/2021 / 39

· Abbreviations and acronyms:

EC50: effective concentration, 50 percent (in vivo) OECD: Organisation for Economic Co-operation and Development STOT: specific target organ toxicity SE: single exposure RE: repeated exposure EC50: half maximal effective concentration IC50: hallf maximal inhibitory concentration NOEL or NOEC: No Observed Effect Level or Concentration $\mathsf{ACGIH}^{\scriptscriptstyle \Theta}$ - American Conference of Governmental Industrial Hygienists •A1 - Confirmed human carcinogen •A2 - Suspected human carcinogen •A3 - Confirmed animal carcinogen with unknown relevance to humans •A4 - Not classifiable as a human carcinogen •A5 - Not suspected as a human carcinogen IARC - International Agency for Research on Cancer •Group 1 - Carcinogenic to humans •Group 2A - Probably carcinogenic to humans •Group 2B - Possibly carcinogenic to humans •Group 3 - Not classifiable as to carcinogenicity to humans •Group 4 - Probably not carcinogenic to humans NTP - National Toxicology Program, U.S. Department of Health and Human Services •Group K - Known to be Human Carcinogens •Group R - Reasonably Anticipated to be Human Carcinogens IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value

Printing date 04/23/2021

Trade name: Hardness Y / N

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 3: Acute toxicity – Category 3 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· Sources

Data arise from safety data sheets, reference works and literature. GESTIS- Stoffdatenbank (Substance Database, Germany) RTECS (Registry of Toxic Effects of Chemical Substances)

 \cdot * Data compared to the previous version altered.

Reviewed on 04/23/2021

(Contd. of page 7)

US -