## Lovibond® Water Testing

## Tintometer® Group



## Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 05/23/2023 Reviewed on 05/23/2023

## 1 Identification

· Product identifier

· Trade name: Reference Standard Saybolt Colour 0 / EC 3000 Saybolt Validation Liquid

· Catalogue number: 134050, 135029

· Application of the substance / the mixture: Coloured Standard Solution for calibration purposes

· Manufacturer/Supplier:

Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 USA

phone: (941) 756-6410 fax: (941) 727-9654 www.lovibond.us Made in UK

· Emergency telephone number: + 1 866 928 0789 (English, French, Spanish)

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 1B H350 May cause cancer.

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Hazard Communication Standard (HCS).
- · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

White mineral oil (petroleum)

Base oil: residual oils solvent-dewaxed

(D94/69 p1345) L Hazard statements

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P201 Obtain special instructions before use.

P301+P310 If swallowed: Immediately call a poison center/doctor. P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container to an approved waste disposal plant.

· Other hazards No further relevant information available.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of organic compounds

(Contd. on page 2)

Printing date 05/23/2023 Reviewed on 05/23/2023

### Trade name: Reference Standard Saybolt Colour 0 / EC 3000 Saybolt Validation Liquid

(Contd. of page 1)

### · Composition and Information on Ingredients:

Percent ranges are used due to the confidential product information.

CAS: 8042-47-5 EINECS: 232-455-8	White mineral oil (petroleum)	Aspiration Hazard 1, H304	80-100%
	(D94/69 p1345) L	Carcinogenicity 1B, H350	1-<3%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

## 4 First-aid measures

#### · Description of first aid measures

#### · General information:

Personal protection for the First Aider.

Immediately remove any clothing soiled by the product.

#### After inhalation:

Supply fresh air or oxygen.

Call a doctor immediately.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact: Rinse opened eye for several minutes (at least 15 min) under running water. Then consult a doctor.

#### · After swallowing:

Rinse out mouth and then drink 1-2 glasses of water.

Do not induce vomiting; immediately call for medical help.

## Most important symptoms and effects, both acute and delayed

after swallowing and inhalation:

breathing difficulty

coughing

dizziness

gastric or intestinal disorders

## Danger:

Danger of pneumonia.

Danger of pulmonary edema.

#### · Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs.

## 5 Fire-fighting measures

## · Extinguishing media

### Suitable extinguishing agents:

Use fire fighting measures that suit the environment.

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

#### · For safety reasons unsuitable extinguishing agents:

Water with full jet

Large Fire: Use of water spray when fighting fire may be inefficient.

### · Special hazards arising from the substance or mixture

Can burn in fire.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO) and carbon dioxide (CO2)

### Advice for firefighters

#### Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

Printing date 05/23/2023 Reviewed on 05/23/2023

### Trade name: Reference Standard Saybolt Colour 0 / EC 3000 Saybolt Validation Liquid

(Contd. of page 2)

## **6 Accidental release measures**

· Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Ensure adequate ventilation

- · Advice for emergency responders: Protective equipment: see section 8
- Environmental precautions: Do not allow product to reach sewage system or any water course.
- · Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- Precautions for safe handling
- Advice on safe handling:

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Keep ignition sources away - Do not smoke.

Hygiene measures:

Do not inhale gases / fumes / aerosols.

Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing.

Store protective clothing separately.

Wash hands before breaks and at the end of work.

Do not eat, drink or smoke when using this product.

- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: see chapter 10
- Further information about storage conditions:

Store locked up or with access restricted to technical experts or their assistants.

Ensure that persons do not handle until all safety precautions have been read and understood.

Protect from heat and direct sunlight.

Protect from exposure to the light.

Protect from humidity and water.

- Recommended storage temperature: 23°C +/- 5°C (65 82°F)
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

· Personal protective equipment:

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled.

- · Breathing equipment: Use respiratory protective device against the effects of fume/dust/aerosol.
- Recommended filter device for short term use: Filter A
- · Protection of hands:

Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

(Contd. on page 4)

Printing date 05/23/2023 Reviewed on 05/23/2023

### Trade name: Reference Standard Saybolt Colour 0 / EC 3000 Saybolt Validation Liquid

(Contd. of page 3)

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves
 Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.11$  mm

Penetration time of glove material

Value for the permeation: Level  $\leq 1$  (10 min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

Use protective goggles that have been tested and approved in accordance with government standards (like NIOSH).

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment:

Do not allow product to reach sewage system or any water course.

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· Appearance:

Form / Physical state:
Color:
Odor:
Characteristic
Odor threshold:
Not determined.

• **pH-value:** Mixture is non-soluble (in water).

· Melting point/freezing point: Not determined.

Initial boiling point and boiling range: 218–800°C (424.4–1472°F) (CAS: 8042-47-5 White mineral oil

(petroleum))

• Flash point: >112°C (>233.6°F) (CAS: 8042-47-5 White mineral oil (petroleum))

Flammability (solid, gas): Can burn in fire.

Auto igniting: >300°C (>572°F) (CAS: 8042-47-5 White mineral oil (petroleum))

· **Decomposition temperature:** Not applicable.

• Auto-ignition temperature: Product is not self-igniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

· Flammability or explosive limits:

Lower:Not determined.Upper:Not determined.

· Oxidizing properties: none

· Vapor Pressure: Not determined.

Density at 20°C (68°F): >0.67-<1.09 g/cm³ (>5.59-<9.1 lbs/gal)

Relative density: Not determined.
Vapor density: Not determined.
Evaporation rate: Not determined.

Solubility(ies)

• Water: Not miscible or difficult to mix. • Partition coefficient (n-octanol/water): Not applicable (mixture).

· Viscosity:

• Kinematic at 40°C (104°F): <20.5 mm<sup>2</sup>/s

Other information

· Solids content: 0 %

· Information with regard to physical hazard classes

· Corrosive to metals none

## 10 Stability and reactivity

- · Reactivity Fumes can combine with air to form an explosive mixture.
- · Chemical stability Stable at ambient temperature (room temperature).
- Possibility of hazardous reactions

Reacts with oxidizing agents.

Explosion hazard with: Nitrates, chlorates, perchlorates

· Conditions to avoid Strong heating (decomposition)

(Contd. on page 5)

Printing date 05/23/2023 Reviewed on 05/23/2023

## Trade name: Reference Standard Saybolt Colour 0 / EC 3000 Saybolt Validation Liquid

(Contd. of page 4)

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: see section 5

## 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values that are relevant for classification:				
CAS: 8042-47-5 White mineral oil (petroleum)					
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50.	>2000 mg/kg (rabbit)			
Inhalative	LC50.	>5 mg/l4h (rat)			
CAS: 64742-62-7 Base oil : residual oils solvent-dewaxed (D94/69 p1345) L					
Oral	LD50	>5000 mg/kg (rat) (OECD 401)			
Dermal	LD50.	>2000 mg/kg (rat)			
Inhalative	LC50.	>5.53 mg/l4h (rat) (OECD 403) (ECHA: there was no mortality in either control or exposed group during the study; aerosol; read-across based on grouping of substances (category approach))			

- · Primary irritant effect:
- · on the skin: Based on available data, the classification criteria are not met.
- on the eye: Based on available data, the classification criteria are not met.
- · Information on components:

## CAS: 8042-47-5 White mineral oil (petroleum)

Irritation of skin OECD 404 (rabbit: no irritation)
Irritation of eyes OECD 405 (rabbit: no irritation)

- · Sensitization: Based on available data, the classification criteria are not met.
- · Information on components:

CAS: 8042-47-5 White mineral oil (petroleum)

Sensitization OECD 406 (guinea pig: negative) (Magnusson / Klingman)

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · Other information: see section 8 / 15
- Synergistic Products: None
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

The following statements refer to the mixture:

Carcinogenicity 1B

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity May cause cancer.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · Information on components:

OECD 414: Teratogenicity testing

OECD 473: Mutagenicity testing

OECD 471, 474, 476, 487: Germ cell mutagenicity testing

Printing date 05/23/2023 Reviewed on 05/23/2023

### Trade name: Reference Standard Saybolt Colour 0 / EC 3000 Saybolt Validation Liquid

(Contd. of page 5)

#### CAS: 8042-47-5 White mineral oil (petroleum)

OECD 471 (negative) (Bacterial Reverse Mutation Test - Ames test)
OECD 474 (negative) (Mammalian Erythrocyte Micronucleus Test)

- · Additional toxicological information:
- · Other information Other dangerous properties can not be excluded.

## 12 Ecological information

· Toxicity

· Aquatic toxicity:

## CAS: 8042-47-5 White mineral oil (petroleum)

EC50 >100 mg/l/48h (Daphnia magna) (OECD 202)

IC50 ≥100 mg/l/72h (Pseudokirchneriella subcapitata) (OECD 201)

LC50 >1000 mg/l/96h (gold orfe) (OECD 203)

## CAS: 64742-62-7 Base oil : residual oils solvent-dewaxed

(D94/69 p1345) L

EC50 >1000 mg/l/48h (Daphnia magna) LC50 >5000 mg/l/96h (rainbow trout)

Persistence and degradability

### CAS: 8042-47-5 White mineral oil (petroleum)

OECD 301 F 31.3 % / 28 d (.)

· Bioaccumulative potential

Pow = n-octanol/wasser partition coefficient

log Pow > 3 = May be accumulated in organism

#### CAS: 8042-47-5 White mineral oil (petroleum)

log Pow >6 (.)

- Mobility in soil No further relevant information available.
- · Other adverse effects Avoid transfer into the environment.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

· UN-Number · DOT, IMDG, IATA	none			
· UN proper shipping name · DOT, IMDG, IATA	none			
· Transport hazard class(es)				
DOT, IMDG, IATA				
· Class	none			
· Packing group				
· DOT, IMDG, IATA	none			
· Environmental hazards:	Not applicable.			

(Contd. on page 7)

Printing date 05/23/2023 Reviewed on 05/23/2023

Trade name: Reference Standard Saybolt Colour 0 / EC 3000 Saybolt Validation Liquid

(Contd. of page 6)

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of MARPOL73/78

and the IBC Code Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (Extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

None of the ingredients is listed.

· New Jersey Special Hazardous Substance List:

None of the ingredients is listed.

Pennsylvania Right-to-Know List:

None of the ingredients is listed.

· Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Information about limitation of use:

Observe national regulations where applicable:

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

H350 May cause cancer.

Printing date 05/23/2023 Reviewed on 05/23/2023

### Trade name: Reference Standard Saybolt Colour 0 / EC 3000 Saybolt Validation Liquid

(Contd. of page 7)

- · Recommended restriction of use: professional/industrial use only
- · Version number / date of revision: 5 / 05/23/2023
- · Abbreviations and acronyms:

OECD: Organisation for Economic Co-operation and Development

STOT: specific target organ toxicity

SE: single exposure

RE: repeated exposure EC50: half maximal effective concentration IC50: half maximal inhibitory concentration

NOEL or NOEC: No Observed Effect Level or Concentration ACGIH® - American Conference of Governmental Industrial Hygienists

•A1 - Confirmed human carcinogen •A2 - Suspected human carcinogen

•A3 - Confirmed animal carcinogen with unknown relevance to humans

•A4 - Not classifiable as a human carcinogen

•A5 - Not suspected as a human carcinogen

IARC - International Agency for Research on Cancer
•Group 1 - Carcinogenic to humans

•Group 2A - Probably carcinogenic to humans

•Group 2B - Possibly carcinogenic to humans

•Group 3 - Not classifiable as to carcinogenicity to humans
•Group 4 - Probably not carcinogenic to humans
NTP - National Toxicology Program, U.S. Department of Health and Human Services
•Group K - Known to be Human Carcinogens

•Group R - Reasonably Anticipated to be Human Carcinogens

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

Carcinogenicity 1B: Carcinogenicity - Category 1B Aspiration Hazard 1: Aspiration hazard - Category 1

- · Sources Data arise from safety data sheets, reference works and literature.
- ·\* Data compared to the previous version altered.