Tintometer[®] Group Water Testing



Page 1/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.10.2023

Version number 1

Revision: 30.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name: Calibration Solution Redox 470 mV
- · Catalog number: 424498, 195070, 195070-0
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation: Standard Solution for calibration purposes
- · 1.3 Details of the supplier of the safety data sheet
- Supplier: Tintometer GmbH Schleefstraße 8-12 44287 Dortmund Made in Germany www.lovibond.com

The Tintometer Limited Lovibond[®]House Sun Rise Way Amesbury Wiltshire SP4 7GR United Kingdom

- Informing department: e-mail: sds@lovibond.com Product Safety Department
- **1.4 Emergency telephone number:** +44 1235 239670 Languages: English

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Met. Corr.1 H290 May be corrosive to metals.



Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



· Signal word Warning

phone: +49 (0)231 94510-0 e-mail: sales@lovibond.com

phone : +44 1980 664800 e-mail: SDS@lovibond.uk

Version number 1

Product name: Calibration Solution Redox 470 mV

(Contd. of page 1)

Revision: 30.10.2023

· Hazard statements

Printing date 30.10.2023

H290 May be corrosive to metals.

H315 Causes skin irritation.

- H319 Causes serious eye irritation.
- Precautionary statements

P280 Wear protective gloves / eye protection.

- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

- P337+P313 If eye irritation persists: Get medical advice/attention.
- P390 Absorb spillage to prevent material damage.

· 2.3 Other hazards No further relevant information available.

· Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

Determination of endocrine-disrupting properties

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: sulfuric acid solution

rous components

Dangerous components:			
CAS: 7664-93-9	sulphuric acid	5–10%	
EINECS: 231-639-5	Met. Corr.1, H290; Skin Corr. 1A, H314		
Index No: 016-020-00-8	Specific concentration limits: Skin Corr. 1A; H314: C ≥ 15 %		
Reg.nr.: 01-2119458838-20-XXXX	Skin Irrit. 2; H315: 5 % ≤ C < 15 %		
	Eye Dam. 1; H318: C ≥ 15 %		
	Eye Irrit. 2; H319: 5 % ≤ C < 15 %		

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact
- Instantly rinse with water. If skin irritation continues, consult a doctor.
- After eye contact Rinse opened eye for several minutes (at least 15 min) under running water. Then consult doctor.
- · After swallowing

Rinse out mouth and then drink 1-2 glasses of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed:

irritations

after inhalation:

mucosal irritations, cough, shortness of breath

after swallowing:

sickness

vomiting

diarrhoea

· Danger Danger of system failure.

• 4.3 Indication of any immediate medical attention and special treatment needed: No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

Version number 1

Product name: Calibration Solution Redox 470 mV

\cdot 5.2 Special hazards arising from the substance or mixture

The product is not combustible. Formation of toxic gases is possible during heating or in case of fire. Can be released in case of fire: Sulphur oxides (SOx) Nitrogen oxides (NOx) • **5.3 Advice for firefighters** • **Protective equipment:** Wear self-contained breathing apparatus.

Wear full protective suit.

· Additional information

Printing date 30.10.2023

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- · Advice for non-emergency personnel:
- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- · Advice for emergency responders: Protective equipment: see section 8
- · 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent. Absorb with liquid-binding material (sand, diatomite, universal binders). Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

• Advice on safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Hygiene measures:

Avoid contact with the skin. Avoid contact with the eyes. Take off immediately all contaminated clothing. Wash hands during breaks and at the end of the work. Do not eat, drink or smoke when using this product.

· 7.2 Conditions for safe storage, including any incompatibilities

- Requirements to be met by storerooms and containers:
- Store in cool location.
- Keep only in original packaging.
- Information about storage in one common storage facility: Store away from metals.
- Do not store together with alkalis (caustic solutions).
- Further information about storage conditions:
- Protect from heat and direct sunlight.
- Protect from the effects of light.
- Protect from humidity and keep away from water. • Recommended storage temperature: 20°C +/- 5°C
- · 7.3 Specific end use(s) No further relevant information available.

Revision: 30.10.2023

(Contd. of page 2)

Version number 1

Revision: 30.10.2023

Product name: Calibration Solution Redox 470 mV

(Contd. of page 3)

SECTION 8: Exposu	re controls/personal protection		
· 8.1 Control parameters			
· Components with limit values that require monitoring at the workplace:			
CAS: 7664-93-9 sulphuric acid			
	Long-term value: 0.05* mg/m³ *mist: defined as thoracic fraction		
	Long-term value: 0.05 mg/m³		
• Regulatory information WEL (Great Britain): EH40 IOELV (European Union): (• Additional information: IC			
· DNELs Derived No Effect Level (D	NEL)		
CAS: 7664-93-9 sulphuric			
	n³ (Worker / acute / local effects)		
	/m³ (Worker / acute / systemic effects)		
Recommended monitorir Methods for measurement DIN EN 689. PNECs	ng procedures: of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and		
Predicted No Effect Conce			
CAS: 7664-93-9 sulphuric			
0.00025 mg/l (Mari 0.0025 mg/l (Fresh PNEC 0.002 mg/kg (Marin	PNEC 8.8 mg/l (Sewage treatment plant) 0.00025 mg/l (Marine water) 0.0025 mg/l (Fresh water) PNEC 0.002 mg/kg (Marine sediment) 0.002 mg/kg (Fresh water sediment)		
	The lists that were valid during the compilation were used as basis.		
	The lists that were valid during the compliation were used as basis.		
• 8.2 Exposure controls • Engineering measures: Technical measures and a See item 7.	ppropriate working operations should be given priority over the use of personal protective equipment.		
Protective clothing should l substances handled. Eye/face protection Safet Hand protection Protective gloves.	asures, such as personal protective equipment be selected specifically for the workplace, depending on concentration and quantity of the hazardous ty glasses by use of skin-protecting agents is recommended.		
After use of gloves apply skin-cleaning agents and skin cosmetics. Material of gloves nitrile rubber, NBR Recommended thickness of the material: ≥ 0.11 mm Penetration time of glove material			
 Value for the permeation: Level = 1 (< 10 min) The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Other skin protection (body protection): Protective work clothing. Breathing equipment: Use breathing protection against the effects of fumes/dust/aerosol. Recommended filter device for short term use: Filter P2 			
· Environmental exposure	controls Do not allow product to reach sewage system or water bodies.		
SECTION 9: Physica	I and chemical properties		
 9.1 Information on basic Physical state 	physical and chemical properties Fluid		

Printing date 30.10.2023

Printing date 30.10.2023

Version number 1

Revision: 30.10.2023

Product name: Calibration Solution Redox 470 mV

- Formu	
· Form:	Solution
· Colour:	Yellowish
· Odour:	Odourless
· Odour threshold:	Not applicable.
 Melting point/Freezing point: 	Not determined.
Boiling point or initial boiling point and boiling range	Not determined.
Flammability	The product is not combustible.
· Explosive properties:	Product is not explosive.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Auto-ignition temperature:	Not applicable.
Decomposition temperature:	Not determined.
pH at 20°C	< 1
	Strongly acidic
· Kinematic viscosity	Not determined.
· Solubility	
· Water:	Fully miscible
 Partition coefficient n-octanol/water (log value) 	Not applicable (mixture).
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20°C:	~1.14 g/cm³
Relative density:	Not determined.
· Relative gas density	Not determined.
Particle characteristics	Not applicable (liquid).
· 9.2 Other information	
· Information with regard to physical hazard classes	
Corrosive to metals	May be corrosive to metals.
• Metals that are corroded by the substance or mixture	Information on incompatible materials can be found in Sections 7 and
	10.
Other safety characteristics	
Oxidising properties:	none
Additional information	
Solids content:	< 10 %
Solvent content:	
Organic solvents:	0 %
· Water:	> 80 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity see section 10.3

· 10.2 Chemical stability Stable at ambient temperature (room temperature).

10.3 Possibility of hazardous reactions

Reacts with metals forming hydrogen (Danger of explosion in case of large amounts!)

Corrosive action on metals

Heating occurs when water is added

Reacts with reducing agents

Reacts with acids and alkali (lyes).

Reacts with ammonia (NH₃).

- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** metals combustible substances

organic solvents

• 10.6 Hazardous decomposition products: see section 5

Version number 1

Revision: 30.10.2023

Product name: Calibration Solution Redox 470 mV

(Contd. of page 5)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:		
CAS: 7664-93-9 sulphuric acid		
Oral		2140 mg/kg (rat) (IUCLID)
Inhalative	LC 50	510 mg/m³/2h (rat) IUCLID

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

Information on components:

Printing date 30.10.2023

Skin irritation testing performed on 10% sulfuric acid showed slight to no irritation effects (GESTIS).

CAS 7664-93-9: chronic: dermatitis

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

· Information on likely routes of exposure

The intake of sulfuric acid is mainly to be expected via the inhalative pathway in the form of aerosols. No studies on absorbability are available.

Generally, local reactions cause the main effects.

Following impact to the skin strong local effects are the main issue. There is no indication of absorption of relevant amounts of S. via the intact skin.

Absorbability via the gastrointestinal tract is assumed. However, no studies on the kinetics of uptake are available. [GESTIS]

Additional toxicological information:

Vapours and aerosols may be irritant to the mucous membranes and upper respiratory tract.

CAS: 7664-93-9 sulphuric acid

(source: GESTIS)

Main toxic effects

Acute: Irritation up to chemical burns to the mucous membranes and skin, danger of serious damage to the eyes and lungs Chronic: Irritation to the eyes and airways, erosion of the teeth, damage to the skin

Further Information:

Concentrated S. differs considerably from dilute Sulfuric acid with regard to chemical properties and effects. With increased dilution Sulfuric acid acts less aggressively.

· 11.2 Information on other hazards

• Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

• Other information

According to the information available to us, the chemical, physical and toxicological properties of the substances mentioned in Chapter 3 have not been thoroughly investigated.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquat	ic toxicity:
CAS:	7664-93-9 sulphuric acid
	>100 mg/l/48h (Daphnia magna) (OECD 202) (ECHA)
	16–29 mg/l/96h (bluegill) (Merck)
· Bacte	rial toxicity: sulphates toxic > 2.5 g/l

Version number 1

Revision: 30.10.2023

Product name: Calibration Solution Redox 470 mV

· Other information:

Toxic for fish: Sulphates > 7 g/l NH₄⁺ > 0.3 mg/l the following applies to dissolved iron compounds in general: toxic as from 0.9 mg/l at pH 6.5 - 7.5 lethal as from 1.0 mg/l at pH 5.5 - 6.7

- 12.2 Persistence and degradability
- · Other information:

Mixture of inorganic compounds.

- Methods for the determination of biodegradability are not applicable to inorganic substances.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

- Avoid transfer into the environment.
- · Water hazard:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to disposers of hazardous waste.

· European waste catalogue

16 05 07* discarded inorganic chemicals consisting of or containing hazardous substances

Uncleaned packagings:

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport informat	ion	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN2796	
 14.2 UN proper shipping name ADR IMDG, IATA 	2796 SULPHURIC ACID mixture SULPHURIC ACID mixture	
· 14.3 Transport hazard class(es)		
ADR		
No. 200		
Class	8 (C1) Corrosive substances.	
· Label	8	
		(Contd. on page 8

(Contd. of page 6)

Version number 1

Revision: 30.10.2023

Product name: Calibration Solution Redox 470 mV

	(Contd. of page
· IMDG, IATA	
· Class · Label	8 Corrosive substances. 8
· 14.4 Packing group · ADR, IMDG, IATA	II
 14.5 Environmental hazards: Marine pollutant: 	No
 • 14.6 Special precautions for user • Kemler Number: • EMS Number: • Segregation groups • Stowage Category 	Warning: Corrosive substances. 80 F-A,S-B (SGG1) Acids B
14.7 Maritime transport in bulk according instruments	to IMO Not applicable.
· Transport/Additional information:	
 ADR Excepted quantities (EQ): Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code 	E1 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act UK

Regulated explosives precursors

The concentration of the substance is less than the stated mass percentage and should still be considered as reportable substance:

CAS: 7664-93-9 sulphuric acid

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

· Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148:

All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see https://ec.europa.eu

explosives precursors - ANNEX I

CAS 7664-93-9: c < 15%

CAS: 7664-93-9 sulphuric acid

(Contd. on page 9) GB

15%

Version number 1

Revision: 30.10.2023

Product name: Calibration Solution Redox 470 mV

Printing date 30.10.2023

Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (PIC)	
None of the ingredients is listed.	
Regulation (EC) No 1334/2000 setting up a Community regime for the control of exports of dual-use technology:	items and
None of the ingredients is listed.	
Regulation (EC) No 273/2004 on drug precursors	
CAS: 7664-93-9 sulphuric acid	
Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community a in drug precursors	and third countrie
CAS: 7664-93-9 sulphuric acid	
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer:	
None of the ingredients is listed.	
REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)	
None of the ingredients is listed.	
LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV)	
None of the ingredients is listed.	
Substances of very high concern (SVHC) according to REACH, Article 57 This product does not contain any substances of very high concern above the legal concentration limit of \geq (Substances of very high concern (SVHC) according to UK REACH This product does not contain any substances of very high concern above the legal concentration limit of \geq (, , ,

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· Information about limitation of use: Not required.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Training hints Provide adequate information, instruction and training for operators.

· Relevant phrases

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Abbreviations and acronyms:

EC50: effective concentration, 50 percent (in vivo) OECD: Organisation for Economic Co-operation and Development

STOT: specific target organ toxicity

- SE: single exposure
- RE: repeated exposure

EC50: half maximal effective concentration

IC50: half maximal inhibitory concentration

NOEL or NOEC: No Observed Effect Level or Concentration ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals - Category 1

Version number 1

Revision: 30.10.2023

Product name: Calibration Solution Redox 470 mV

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

· Sources

Data arise from safety data sheets, reference works and literature. ECHA: European CHemicals Agency http://echa.europa.eu IUCLID (International Uniform Chemical Information Database) GESTIS- Stoffdatenbank (Substance Database, Germany)

** Data compared to the previous version altered.

(Contd. of page 9)

GB —

Printing date 30.10.2023