Lovibond[®] Water Testing

Tintometer® Group



Reviewed on 02/15/2019

Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 02/15/2019

1 Identification

· Product identifier

- · Trade name: Vario Sodium hydroxide 1N
- · Catalogue number: 531520, 4531520, 531520-0
- · Application of the substance / the mixture: Reagent for water analysis

Manufacturer/Supplier: Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 USA phone: (941) 756-6410 fax: (941) 727-9654 www.lovibond.us Made in Germany

· Emergency telephone number: + 1 866 928 0789 (English, French, Spanish)

2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

· Label elements

• **GHS label elements** The product is classified and labeled according to the Hazard Communication Standard (HCS). • **Hazard pictograms**



· Signal word Danger

- · Hazard statements
- H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P310 Immediately call a poison center/doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

 \cdot Other hazards No further relevant information available.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** aqueous solution

Printing date 02/15/2019

Reviewed on 02/15/2019

Trade name: Vario Sodium hydroxide 1N

· Composition and Informati Percent ranges are used due	on on Ingredients: to the confidential product info	rmation.	(Co	ontd. of page 1)
CAS: 1310-73-2 EINECS: 215-185-5 Index number: 011-002-00-6 RTECS: WB4900000	sodium hydroxide the wording of the listed hazar		♦ Met. Corr.1, H290	2.5–5%
4 First-aid measures				
 After inhalation: Supply fresh air. Call a doctor immediately. After skin contact: Immediately wash with polyed Immediately rinse with plenty Immediate medical treatment After eye contact: Rinse opened eye for severa Call a doctor immediately. After swallowing: Rinse out mouth and then dri Do not induce vomiting; immediate burns after inhalation: coughing breathing difficulty damage to the affected muco after swallowing: strong caustic effect pain Indication of any immediated 	diately remove any clothing soil hylene glycol 400. of water. necessary. Failure to treat bur minutes (at least 15 min) under nk 1-2 glasses of water. ediately call for medical help. and effects, both acute and c us membranes possible e medical attention and spec niting, danger of entering the lu	ns can prevent wounds from he er running water. Ielayed	aling.	

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- The product is not combustible.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

- Wear fully protective suit.
- Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

6 Accidental release measures

 \cdot Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Ensure adequate ventilation

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 02/15/2019

Reviewed on 02/15/2019

Trade name: Vario Sodium hydroxide 1N

Use respiratory protective device against the effects of fumes/dust/aerosol.

- Advice for emergency responders: Protective equipment: see section 8
- Environmental precautions: Do not allow product to reach sewage system or any water course.
- Methods and material for containment and cleaning up:

Ensure adequate ventilation. Use neutralizing agent.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

- · Advice on safe handling: No special precautions are necessary if used correctly.
- · Hygiene measures:

Do not inhale gases / fumes / aerosols.

Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing.

Wash hands before breaks and at the end of work.

Do not eat, drink or smoke when using this product.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility:
- Store away from metals.
- Do not store together with acids.
- Further information about storage conditions: Protect from heat and direct sunlight.
- Protect from exposure to the light.
- Protect from humidity and water.
- Recommended storage temperature: 20°C +/- 5°C (approx. 68°F)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:			
CAS: 1310-73	CAS: 1310-73-2 sodium hydroxide		
PEL (USA)	Long-term value: 2 mg/m³		
REL (USA)	Ceiling limit value: 2 mg/m³		
TLV (USA)	Ceiling limit value: 2 mg/m³		
EL (Canada)	Ceiling limit value: 2 mg/m³		
EV (Canada)	Ceiling limit value: 2 mg/m³		

· Additional information: The lists that were valid during the creation were used as basis.

· Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

- · Personal protective equipment:
- · Breathing equipment: Use respiratory protective device against the effects of fumes/dust/aerosol.
- Recommended filter device for short term use: Filter P2
- Protection of hands:
- Alkaline resistant gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

Printing date 02/15/2019

Reviewed on 02/15/2019

Trade name: Vario Sodium hydroxide 1N

· Penetration time of glove material

Value for the permeation: Level \leq 1 (10 min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Tightly sealed goggles

· Body protection: Protective work clothing

• Limitation and supervision of exposure into the environment: Do not allow product to reach sewage system or any water course.

9 Physical and chemical properties

· Information on basic physical and chemical properties		
 Appearance: Form / Physical state: Color: 	Fluid Colorless	
· Odor: · Odor threshold:	Odorless Not applicable.	
[·] pH-value at 20°C (68°F):	~ 13 Strongly acidic	
 Melting point/freezing point: Initial boiling point and boiling range: 	Not determined. ~100°C (~212°F)	
· Flash point:	Not applicable.	
· Flammability (solid, gas):	Not applicable.	
· Decomposition temperature:	Not applicable.	
· Auto-ignition temperature:	Product is not self-igniting.	
Danger of explosion: Flammability or explosive limits:	Product does not present an explosion hazard.	
Lower: Upper:	Not applicable. Not applicable.	
· Oxidizing properties:	none	
 Vapor Pressure: Density at 20°C (68°F): Relative density: Vapor density: Evaporation rate: 	Not determined. 1.04 g/cm³ (8.68 lbs/gal) Not determined. Not determined. Not determined.	
· Solubility(ies) Water:	Fully miscible.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:	Not determined.	
 Solvent content: Organic solvents: Water: Solids content: 	0.0 % > 95 % < 5 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity see section "Possibility of hazardous reactions"

· Chemical stability Stable at ambient temperature (room temperature).

Possibility of hazardous reactions

Corrosive action on metals.

Reacts with metals forming hydrogen (Danger of explosion!)

Corrodes aluminium and zinc.

Exothermic reaction with acids.

(Contd. of page 3)

Printing date 02/15/2019

Reviewed on 02/15/2019

Trade name: Vario Sodium hydroxide 1N

· Conditions to avoid No further relevant information available.	(Contd. of page 4
· Incompatible materials:	
metals	
light metals	
aluminum zinc	
organic substances	
· Hazardous decomposition products: see section 5	
1 Toxicological information	
 Information on toxicological effects Acute toxicity: Based on available data, the classification criteria are not met. 	
· LD/LC50 values that are relevant for classification:	
CAS: 1310-73-2 sodium hydroxide	
Oral LDLo 500 mg/kg (rabbit)	
(IUCLID)	
· Primary irritant effect:	
• on the skin: Causes severe skin burns.	
· on the eye: Causes serious eye damage.	
Risk of blindness!	
• Sensitization: Based on available data, the classification criteria are not met.	
· Information on components:	
CAS: 1310-73-2 sodium hydroxide	
Sensitization Patch test (human) (negative)	
· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
· Other information: see section 8 / 15	

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

• STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met. • STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

· Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12 Ecological information

· Toxicity

Aquatic toxicity:
 CAS: 1310-73-2 sodium hydroxide

LC50 40.4 mg/l/48h (Ceriodaphnia sp.)

(ECHA)

(Contd. on page 6)

(Contd. of page 4)

⁰⁰

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 02/15/2019

Reviewed on 02/15/2019

Trade name: Vario Sodium hydroxide 1N

Bacterial toxicity:

- CAS: 1310-73-2 sodium hydroxide
- EC50 22 mg/l (Photobacterium phosphoreum) (15 min)

Persistence and degradability

- · Other information:
- Mixture of inorganic compounds.
- Methods for the determination of biodegradability are not applicable to inorganic substances.
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Other adverse effects
- Harmful effect due to pH shift.
- Forms corrosive mixtures with water even if diluted.
- Neutralization possible in waste water treatment plants.
- Avoid transfer into the environment.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

JN-Number		
DOT, IMDG, IATA	UN1824	
UN proper shipping name		
DOT	Sodium hydroxide solution	
IMDG, IATA	SODIUM HYDROXIDE SOLUTION	
Transport hazard class(es)		
DOT, IMDG, IATA		
a a a a a a a a a a a a a a a a a a a		
Class	8 Corrosive substances	
Label	8	
Packing group		
DOT, IMĎĞ, IATA	III	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Corrosive substances	
Danger code (Kemler):	80	
EMS Number:	F-A,S-B	
Segregation groups	Alkalis	
Stowage Category	A	
Segregation Code	SG35 Stow "separated from" acids.	
Transport in bulk according to Annex II of I		
and the IBC Code	Not applicable.	

Printing date 02/15/2019

Reviewed on 02/15/2019

Trade name: Vario Sodium hydroxide 1N

	(Contd. of page 6)
· Transport/Additional information:	
·DOT	
 Quantity limitations 	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
·IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara

· Section 355 (Extremely hazardous substances):
None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
· TSCA (Toxic Substances Control Act):
All ingredients are listed.

· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· New Jersey Right-to-Know List:	
CAS: 1310-73-2 sodium hydroxide	
· New Jersey Special Hazardous Substance List:	
CAS: 1310-73-2 sodium hydroxide	CO, R1
· Pennsylvania Right-to-Know List:	
CAS: 1310-73-2 sodium hydroxide	
· Pennsylvania Special Hazardous Substance List:	
CAS: 1310-73-2 sodium hydroxide	E
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

· Information about limitation of use: Employment restrictions concerning young persons must be observed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H290 May be corrosive to metals.

Date of preparation / last revision 02/15/2019 / 12

Printing date 02/15/2019

Reviewed on 02/15/2019

Trade name: Vario Sodium hydroxide 1N

(Contd. of page 7)

US ·

· Abbreviations and acronyms: OECD: Organisation for Economic Co-operation and Development STOT: specific target organ toxicity SE: single exposure RE: repeated exposure EC50: half maximal effective concentration IC50: hallf maximal inhibitory concentration NOEL or NOEC: No Observed Effect Level or Concentration ACGIH[®] - American Conference of Governmental Industrial Hygienists •A1 - Confirmed human carcinogen •A2 - Suspected human carcinogen •A3 - Confirmed animal carcinogen with unknown relevance to humans •A4 - Not classifiable as a human carcinogen •A5 - Not suspected as a human carcinogen IARC - International Agency for Research on Cancer •Group 1 - Carcinogenic to humans •Group 2A - Probably carcinogenic to humans •Group 2B - Possibly carcinogenic to humans •Group 2 - Not classifiable as to carcinogenicity to humans •Group 4 - Probably not carcinogenic to humans NTP - National Toxicology Program, U.S. Department of Health and Human Services •Group K - Known to be Human Carcinogens •Group R - Reasonably Anticipated to be Human Carcinogens IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Met. Corr.1: Corrosive to metals - Category 1 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Sources

Data arise from safety data sheets, reference works and literature. IUCLID (International Uniform Chemical Information Database) ECHA: European CHemicals Agency http://echa.europa.eu

* Data compared to the previous version altered.