Tintometer[®] Group Water Testing



phone: +49 (0)231 94510-0

e-mail: sales@lovibond.com

phone: +44 1980 664800

e-mail: SDS@lovibond.uk

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name: Polyacrylate Buffer A1
- · Catalog number:

56Z025598, 56L025565, 56U025565, 56L025597, 56U025597, 56L02559, 56L025598, 56L025591, 56L025530, 56U025530, SDT082

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation: Reagent for water analysis
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Tintometer GmbH Schleefstraße 8-12 44287 Dortmund Made in Germany www.lovibond.com

The Tintometer Limited Lovibond® House Sun Rise Way Amesbury Wiltshire SP4 7GR United Kingdom

Informing department: e-mail: sds@lovibond.com Product Safety Department

· 1.4 Emergency telephone number:

+44 1235 239670 Languages: English

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

(Contd. of page 1)

· Hazard pictograms





GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

2-aminoethanol

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

Precautionary statements

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

· 2.3 Other hazards

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

CAS 141-43-5: Danger by skin resorption.

Vapours of the product are heavier than air and may accumulate on the ground, in mines, drains or cellars with higher concentration.

· Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

Determination of endocrine-disrupting properties

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: aqueous solution

· Dangerous component	· Dangerous components:		
CAS: 141-43-5	2-aminoethanol	10–20%	
EINECS: 205-483-3 Index No: 603-030-00-8	♦ Skin Corr. 1B, H314; ↑ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335 ATE: LC50/4h inhalative: 11 mg/l Specific concentration limit: STOT SE 3; H335: C ≥ 5 %		
CAS: 2002-24-6	2-hydroxyethylammonium chloride	5–<10%	
EINECS: 217-900-6	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		

[·] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation Supply fresh air or oxygen; call for doctor.
- After skin contact

Wash with plenty of water.

If present, better wash with 5 % acetic acid solution, then rinse with water.

Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.

After eye contact

Rinse opened eye for several minutes (at least 15 min) under running water.

Call a doctor immediately.

After swallowing

Rinse out mouth and then drink 1-2 glasses of water.

(Contd. of page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

Do not induce vomiting; instantly call for medical help.

4.2 Most important symptoms and effects, both acute and delayed:

burns

after inhalation:

breathing difficulty

coughing

damage to the affected mucous membranes possible

after swallowing:

strong caustic effect.

sickness

vomiting

pain

- · Danger Danger of gastric perforation.
- 4.3 Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs

Subsequent observation for pneumonia and pulmonary oedema

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Water, Carbon dioxide (CO2), Foam, Fire-extinguishing powder
- For safety reasons unsuitable extinguishing agents

For this substance / mixture no limitations of extinguishing agents are given.

· 5.2 Special hazards arising from the substance or mixture

combustible

Formation of toxic gases is possible during heating or in case of fire.

Can be released in case of fire:

Nitrogen oxides (NOx)

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Ensure adequate ventilation

Use breathing protection against the effects of fumes/dust/aerosol.

- · Advice for emergency responders: Protective equipment: see section 8
- · 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep containers tightly sealed.

Prevent formation of aerosols.

(Contd. on page 4)

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

(Contd. of page 3)

Ensure good ventilation/exhaustion at the workplace.

· Advice on safe handling: Prevent formation of aerosols.

Hygiene measures:

Do not inhale gases / fumes / aerosols.

Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing.

Wash hands during breaks and at the end of the work.

Do not eat, drink or smoke when using this product.

· 7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and containers:

Store in cool location.

Keep only in original packaging.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Protect from heat and direct sunlight.

Store container in a well ventilated position.

Protect from the effects of light.

Protect from humidity and keep away from water.

- Recommended storage temperature: 20°C +/- 5°C
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with limit values that require monitoring at the workplace:			
CAS: 141-43-5 2-aminoe	CAS: 141-43-5 2-aminoethanol		
WEL (Great Britain)	Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk		
IOELV (European Union)	Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin		

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (European Union): (EU) 2019/1831

DNELs

Derived No Effect Level (DNEL)

Delived IV	Delived No Effect Level (DINEL)	
CAS: 141-43-5 2-aminoethanol		
Oral	DNEL	3.75 mg/kg (Consumer / long-term / systemic effects)
Dermal	DNEL	1 mg/kg (Worker / long-term /systemic effects)
		0.24 mg/kg (Consumer / long-term / systemic effects)
Inhalative	DNEL	3.3 mg/m³ (Worker / long-term / local effects)
		2 mg/m³ (Consumer / long-term / systemic effects)

Recommended monitoring procedures:

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and **DIN EN 689.**

· PNECs

Predicted No Effect Concentration (PNEC)

	41-43-5 2-aminoethanol
PNEC	100 mg/l (Sewage treatment plant)
(0.0085 mg/l (Marine water)
(0.025 mg/l (Aquatic intermittent release)
(0.085 mg/l (Fresh water)
PNEC (0.035 mg/kg (Soil)
(0.0425 mg/kg (Marine sediment)
(0.425 mg/kg (Fresh water sediment)

(Contd. on page 5)

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

(Contd. of page 4)

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

· Individual protection measures, such as personal protective equipment

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled.

Eye/face protection

Tightly sealed safety glasses.

Use safety glasses that have been tested and approved in accordance with government standards such as EN 166.

Hand protection

Protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

Penetration time of glove material

Value for the permeation: Level = 1 (< 10 min)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Other skin protection (body protection): Protective work clothing.
- · Breathing equipment: Use breathing protection against the effects of fumes/dust/aerosol.
- · Recommended filter device for short term use: Combination filter A-P2
- · Environmental exposure controls Avoid release to the environment.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· Physical state · Form: Solution · Colour: Light brown · Odour: Ammonia-like

· Odour threshold: CAS 141-43-5: 2-4 ppm

Melting point/Freezing point: Not determined. · Boiling point or initial boiling point and boiling range Not determined. Flammability Combustible liquid.

Explosive properties: Product is not explosive. However, formation of explosive air/steam

mixtures is possible.

· Lower and upper explosion limit

Not determined. Lower: Upper: Not determined.

· Flash point: >93°C (CAS: 141-43-5 2-aminoethanol)

· Auto-ignition temperature: Not determined. · Decomposition temperature: Not determined. pH at 20°C 10.5

Kinematic viscosity Not determined.

· Solubility

· Water: Fully miscible

· Partition coefficient n-octanol/water (log value) Not applicable (mixture). Not determined.

Vapour pressure:

· Density and/or relative density · Density at 20°C: 1.1 g/cm³ Not determined. · Relative density: · Relative gas density Not determined. · Particle characteristics Not applicable (liquid).

· 9.2 Other information

· Information with regard to physical hazard classes

(Contd. on page 6)

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

(Contd. of page 5)

· Corrosive to metals	May be corrosive to metals.
· Metals that are corroded by the substance or mixture	Information on incompatible materials can be found in Sections 7 and
	10.
Other safety characteristics	
Oxidising properties:	none
Additional information	
· Solids content:	10 - 25 %

Solvent content:
 Organic solvents:
 Water:
 10 - 20 %
 50 - 60 %

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Fumes can combine with air to form an explosive mixture.
- · 10.2 Chemical stability Stable at ambient temperature (room temperature).
- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: aluminium, copper, zinc, metal ions copper rubber
- 10.6 Hazardous decomposition products: see section 5

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

CAS: 141-43-5 2-aminoethanol				
Oral	LD50	1720 mg/kg (rat) (GESTIS)		
Dermal	LD50	1010 mg/kg (rabbit) (GESTIS)		
Inhalative	LC50/4h	11 mg/l (ATE)		

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation

Causes serious eye damage.

Risk of blindness!

· Information on components:

CAS: 1	141-43-5	2-aminoet	hanol
--------	----------	-----------	-------

Irritation of skin OECD 404 (rabbit: burns) (IUCLID)
Irritation of eyes OECD 405 (rabbit: burns) (IUCLID)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Information on components: CAS 141-43-5: Sensitizing effect by skin contact is possible by prolonged/repeated exposure.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · Information on components:

OECD 414: Teratogenicity testing

OECD 473: Mutagenicity testing

OECD 471, 474, 476, 487: Germ cell mutagenicity testing

CAS: 141	CAS: 141-43-5 2-aminoethanol		
OECD 47	(negative) (Bacterial Reverse Mutation Test - Ames test) (Salmonella typhimurium)		
OECD 474	(negative)	(0	

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

(Contd. of page 6)

- · STOT (specific target organ toxicity) -single exposure May cause respiratory irritation.
- STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

· Information on likely routes of exposure

The main route of absorption for 2-aminoethanol (MEA) is through the respiratory tract.

However, the possibility of penetration of the liquid through the skin should not be disregarded. [GESTIS]

· Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

CAS: 141-43-5 2-aminoethanol

(source: GESTIS)

Depending on the concentration and duration of exposure, MEA causes severe irritation or even burns on all contacted mucous membranes and also on the skin, which can occur with a certain delay.

Symptoms of acute poisoning:

Eyes: Conjunctivitis up to damage to the cornea.

Skin: irritation, swelling; chemical burns possible with prolonged exposure to the undiluted substance; sensitization Inhalation: irritation of the airways up to toxic pulmonary edema; even at lower concentrations, pulmonary dysfunction cannot be ruled out; Resorptive effects can occur relatively quickly

Ingestion: (only experience from animal experiments): irritation to damage to mucous membranes that have been contacted; systemic effects

Absorption (only in animal experiments): loss of muscle tone; sedation, dyspnoea, convulsions, damage to blood vessels; Functional changes up to damage to various organs (especially liver, kidneys, lungs).

- · 11.2 Information on other hazards
- Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- Other information

According to the information available to us, the chemical, physical and toxicological properties of the substances mentioned in Chapter 3 have not been thoroughly investigated.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:

CAS: 141-43-5 2-aminoethanol

EC50 65 mg/l/48h (Daphnia magna)

(IUCLID)

IC50 22 mg/l/72h (Desmodesmus subspicatus)

(IUCLID)

LC50 150 mg/l/96h (rainbow trout)

(IUCLID)

· 12.2 Persistence and degradability

CAS: 141-43-5 2-aminoethanol

OECD 301 F 90–100 % / 28 d (readily biodegradable) (Manometric Respirometry)

12.3 Bioaccumulative potential

Pow = n-octanol/wasser partition coefficient

log Pow < 1 = Does not accumulate in organisms.

CAS: 141-43-5 2-aminoethanol

log Pow -1.91 (.) (OECD 107 / 25°C)

CAS: 2002-24-6 2-hydroxyethylammonium chloride

log Pow -4.8 (calculation)

(Merck)

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects Avoid transfer into the environment.

(Contd. on page 8)

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

(Contd. of page 7)

· Water hazard:

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to disposers of hazardous waste.

· European waste catalogue

16 05 06* laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

	N 14: Tra	 a fine wheel and	
	10 14 1		
_			

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN2491
· 14.2 UN proper shipping name · ADR · IMDG, IATA	2491 ETHANOLAMINE SOLUTION ETHANOLAMINE SOLUTION

- · 14.3 Transport hazard class(es)
- · ADR



· Class 8 (C7) Corrosive substances. · Label 8

· IMDG, IATA



· Class 8 Corrosive substances.

· Label 8

· 14.4 Packing group · ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Corrosive substances.

Kemler Number:
EMS Number:
Segregation groups
(SGG18) Alkalis

· Stowage Category A

Segregation Code SG35 Stow "separated from" SGG1-acids

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

· Excepted quantities (EQ): E1

(Contd. on page 9)

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

(Contd. of page 8)

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category 3 · Tunnel restriction code E

· IMDG

· Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act UK
- · Regulated explosives precursors

None of the ingredients is listed.

- · Regulated poisons
- None of the ingredients is listed.
- · Reportable explosives precursors

None of the ingredients is listed.

- · Reportable poisons
- None of the ingredients is listed.
- · Regulation (EU) 2019/1148 on the marketing and use of explosives precursors not regulated
- Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (PIC)

None of the ingredients is listed.

· Regulation (EC) No 1334/2000 setting up a Community regime for the control of exports of dual-use items and technology:

None of the ingredients is listed.

- · Regulation (EC) No 273/2004 on drug precursors
- None of the ingredients is listed.
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer:

None of the ingredients is listed.

· REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)

None of the ingredients is listed.

· LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV)

None of the ingredients is listed.

· Substances of very high concern (SVHC) according to REACH, Article 57

This product does not contain any substances of very high concern above the legal concentration limit of ≥ 0.1% (w / w).

Substances of very high concern (SVHC) according to UK REACH

This product does not contain any substances of very high concern above the legal concentration limit of ≥ 0.1% (w / w).

- Directive 2012/18/EU (SEVESO III):
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Information about limitation of use:

Employment restrictions concerning young persons must be observed (94/33/EC).

Employment restrictions concerning pregnant and lactating women must be observed (92/85/EEC).

(Contd. on page 10)

Printing date 10.11.2023 Version number 7 (replaces version 6) Revision: 10.11.2023

Product name: Polyacrylate Buffer A1

(Contd. of page 9)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Training hints Provide adequate information, instruction and training for operators.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Abbreviations and acronyms:

EC50: effective concentration, 50 percent (in vivo)

OECD: Organisation for Economic Co-operation and Development

STOT: specific target organ toxicity

SE: single exposure

RE: repeated exposure

EC50: half maximal effective concentration

IC50: half maximal inhibitory concentration

NOEL or NOEC: No Observed Effect Level or Concentration
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of

Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Data arise from safety data sheets, reference works and literature.

ECHA: European CHemicals Agency http://echa.europa.eu

IUCLID (International Uniform Chemical Information Database)

GESTIS- Stoffdatenbank (Substance Database, Germany)

* Data compared to the previous version altered.