### **Lovibond® Water Testing**

### Tintometer® Group



### Safety Data Sheet acc. to OSHA HCS (HazCom 2012)

Printing date 02/05/2019 Reviewed on 02/05/2019

### 1 Identification

- · Product identifier
- · Trade name: KS6856 Redox Standard 600mV @ 25°C / ORP 600mV Calibration Solution
- · Catalogue number: 56Z685698, 56L685697, 56U685697, 56L685698, 56U685698
- · Application of the substance / the mixture:

Standard Solution for calibration purposes

Coloured Standard Solution for calibration purposes

· Manufacturer/Supplier:

Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 USA phone: (941) 756-64

phone: (941) 756-6410 fax: (941) 727-9654 www.lovibond.us Made in Germany

· Emergency telephone number: + 1 866 928 0789 (English, French, Spanish)

### 2 Hazard(s) identification

· Classification of the substance or mixture



**GHS05 Corrosion** 

Met. Corr.1 H290 May be corrosive to metals.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- Label elements
- · GHS label elements The product is classified and labeled according to the Hazard Communication Standard (HCS).
- · Hazard pictograms



GHS05

- · Signal word Warning
- · Hazard statements

H290 May be corrosive to metals.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P234 Keep only in original container.

P280 Wear protective gloves / eye protection. P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

Printing date 02/05/2019 Reviewed on 02/05/2019

Trade name: KS6856 - Redox Standard 600mV @ 25°C / ORP 600mV Calibration Solution

(Contd. of page 1)

· Other hazards No further relevant information available.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: sulfuric acid solution
- · Composition and Information on Ingredients:

Cancer Status IARC: Strong inorganic acid mists containing sulphuric acid can cause cancer.

CAS: 7664-93-9	sulphuric acid	♦ Met. Corr.1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318	10-<15%
EINECS: 231-639-5			
Index number: 016-020-00-8			
RTECS: WS5600000			

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately rinse with plenty of water.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes (at least 15 min) under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink 1-2 glasses of water.

If symptoms persist consult doctor.

· Most important symptoms and effects, both acute and delayed

sickness

vomiting

diarrhoea

irritations

after inhalation:

coughing

Causes mild skin irritation.

- · Danger: Danger of pulmonary edema.
- · Indication of any immediate medical attention and special treatment needed: No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

The product is not combustible.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Sulfur oxides (SOx)

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

US-

Printing date 02/05/2019 Reviewed on 02/05/2019

Trade name: KS6856 - Redox Standard 600mV @ 25°C / ORP 600mV Calibration Solution

(Contd. of page 2)

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- · Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Advice for emergency responders: Protective equipment: see section 8
- · Environmental precautions: Do not allow product to reach sewage system or any water course.
- · Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralizing agent.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Precautions for safe handling
- · Advice on safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Hygiene measures:

Avoid contact with the skin.

Avoid contact with the eyes.

Take off immediately all contaminated clothing.

Wash hands before breaks and at the end of work.

Do not eat, drink or smoke when using this product.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility:

Store away from metals.

Do not store together with alkalis (caustic solutions).

Store away from flammable substances.

· Further information about storage conditions:

Protect from heat and direct sunlight.

Protect from exposure to the light.

Protect from humidity and water.

- · Recommended storage temperature: 20°C +/- 5°C (approx. 68°F)
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

# PEL (USA) Long-term value: 1 mg/m³ REL (USA) Long-term value: 1 mg/m³ TLV (USA) Long-term value: 0.2\* mg/m³ \*as thoracic fraction

CAS: 7664-93-9 sulphuric acid

EL (Canada) Long-term value: 0.2 mg/m³

ACGIH A2; IARC 1

EV (Canada) Long-term value: 0.2 mg/m<sup>3</sup>

- · Additional information: The lists that were valid during the creation were used as basis.
- · Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

(Contd. on page 4)

Printing date 02/05/2019 Reviewed on 02/05/2019

#### Trade name: KS6856 - Redox Standard 600mV @ 25°C / ORP 600mV Calibration Solution

(Contd. of page 3)

- · Personal protective equipment:
- · Breathing equipment: Use respiratory protective device against the effects of fumes/dust/aerosol.
- · Recommended filter device for short term use: Filter P2
- · Protection of hands:

Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.11$  mm

· Penetration time of glove material

Value for the permeation: Level  $\leq 1$  (10 min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment: Avoid release to the environment.

9 Physical and chemical properties			
Information on basic physical and che     Appearance:     Form / Physical state:			
Color:	Fluid Light green		
Odor: Odor threshold:	Odorless Not applicable.		
· pH-value at 20°C (68°F):	<1		
<ul> <li>Melting point/freezing point:</li> <li>Initial boiling point and boiling range:</li> </ul>	Not determined. : 100°C (212°F)		
· Flash point:	Not applicable.		
· Flammability (solid, gas): · Ignition temperature:	Not applicable. Not applicable.		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature:	Product is not self-igniting.		
Danger of explosion:     Flammability or explosive limits:     Lower:	Product does not present an explosion hazard.  Not applicable.		
Upper:	Not applicable.		
· Oxidizing properties:	none		
<ul> <li>Vapor Pressure:</li> <li>Density at 20°C (68°F):</li> <li>Relative density:</li> <li>Vapor density:</li> <li>Evaporation rate:</li> </ul>	Not determined. 1.11 g/cm³ (9.26 lbs/gal) Not determined. Not determined. Not determined.		
· Solubility(ies) Water:	Fully miscible.		
· Partition coefficient (n-octanol/water)	· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:	Not determined.		
· Solvent content: Organic solvents:	0.0 %		
· Other information	No further relevant information available.		

Printing date 02/05/2019 Reviewed on 02/05/2019

Trade name: KS6856 - Redox Standard 600mV @ 25°C / ORP 600mV Calibration Solution

(Contd. of page 4)

### 10 Stability and reactivity

- · Reactivity see section "Possibility of hazardous reactions"
- · Chemical stability Stable at ambient temperature (room temperature).
- · Possibility of hazardous reactions

Corrosive action on metals.

Reacts with metals forming hydrogen (Danger of explosion!)

Heating occurs when water is added.

Reacts with reducing agents.

Reacts with oxidizing agents.

Reacts with acids and alkali (lyes).

Reacts with ammonia (NH<sub>3</sub>).

- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

metals

combustible materials

organic solvents

· Hazardous decomposition products: see section 5

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:				
CAS: 7664-93-9 sulphuric acid				
Oral		2140 mg/kg (rat) (IUCLID)		
		510 mg/m³/2h (rat) IUCLID		

- · Primary irritant effect:
- · on the skin: Causes skin irritation.
- · on the eye: Causes serious eye irritation.
- · Information on components:

Skin irritation testing performed on 10% sulfuric acid showed slight to no irritation effects (GESTIS).

CAS 7664-93-9: chronic: dermatitis

- · Sensitization: Based on available data, the classification criteria are not met.
- · Carcinogenic categories

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
CAS: 7664-93-9 sulphuric acid	1
· NTP (National Toxicology Program)	
CAS: 7664-93-9 sulphuric acid	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

#### · Other information:

see section 8 / 15

Cancer Status of Sulfuric acid: The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mists containing sulfuric acid" as a known human carcinogen, (IARC category 1). This classification applies only to mists containing sulfuric acid and not to sulfuric acid or sulfuric acid solutions.

A2 (Suspected for humans) by ACGIH

- · Synergistic Products: None
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction): The following statements refer to the mixture:
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 02/05/2019 Reviewed on 02/05/2019

Trade name: KS6856 - Redox Standard 600mV @ 25°C / ORP 600mV Calibration Solution

(Contd. of page 5)

#### · Additional toxicological information:

The following applies to soluble iron compounds: nausea and vomiting after swallowing. The absorption of large quantities is followed by cardiovascular disorders. Toxic effect on liver and kidneys.

Mists may be irritant to the mucous membranes and upper respiratory tract.

Sulfuric acid: erosion of the teeth, cancer

### 12 Ecological information

· Toxicity

· Aquatic toxicity:

CAS: 7664-93-9 sulphuric acid

EC50 >100 mg/l/48h (Daphnia magna) (OECD 202)

(ECHA)

16-29 mg/l/96h (bluegill) LC50

(Merck)

- · Bacterial toxicity: sulfates toxic > 2.5 g/l
- · Other information:

Toxic for fish:

sulfates > 7 g/l

 $NH_4^+ > 0.3 \text{ mg/l}$ 

the following applies to dissolved iron compounds in general:

toxic as from 0.9 mg/l at pH 6.5 - 7.5

lethal as from 1.0 mg/l at pH 5.5 - 6.7

- · Persistence and degradability .
- · Other information:

Mixture of inorganic compounds.

Methods for the determination of biodegradability are not applicable to inorganic substances.

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Other adverse effects

Harmful effect due to pH shift.

Avoid transfer into the environment.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

· UN-Number · DOT, IMDG, IATA	UN2796
· UN proper shipping name	
· DOT	Sulfuric acid mixture
· IMDG, IATA	SULPHURIC ACID mixture

(Contd. on page 7)

Printing date 02/05/2019 Reviewed on 02/05/2019

Trade name: KS6856 - Redox Standard 600mV @ 25°C / ORP 600mV Calibration Solution

(Contd. of page 6)

· Transport hazard class(es)

· DOT, IMDG, IATA



· Class 8 Corrosive substances

· Label 8

· Packing group

· DOT, IMDG, IATA

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Corrosive substances

Danger code (Kemler):
EMS Number:
Segregation groups
Stowage Category

80
F-A,S-B
Acids
B

 $\cdot$  Transport in bulk according to Annex II of MARPOL73/78

and the IBC Code Not applicable.

· Transport/Additional information:

· DO1

• Quantity limitations On passenger aircraft/rail: 1 L

On cargo aircraft only: 30 L

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)1LCode: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (Extremely hazardous substances):

CAS: 7664-93-9 sulphuric acid

· Section 313 (Specific toxic chemical listings):

CAS: 7664-93-9 sulphuric acid

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· New Jersey Right-to-Know List:

CAS: 7664-93-9 sulphuric acid

· New Jersey Special Hazardous Substance List:

CAS: 7664-93-9 sulphuric acid

CA, CO, R2

Printing date 02/05/2019 Reviewed on 02/05/2019

#### Trade name: KS6856 - Redox Standard 600mV @ 25°C / ORP 600mV Calibration Solution

(Contd. of page 7)

· Pennsylvania Right-to-Know List:

CAS: 7664-93-9 sulphuric acid

· Pennsylvania Special Hazardous Substance List:

CAS: 7664-93-9 sulphuric acid

Ε

EPA (Environmental Protection Agency)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · Information about limitation of use: Employment restrictions concerning young persons must be observed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

· Date of preparation / last revision 02/05/2019 / 2

· Abbreviations and acronyms:

OECD: Organisation for Economic Co-operation and Development

STOT: specific target organ toxicity

SE: single exposure RE: repeated exposure

EC50: half maximal effective concentration IC50: hallf maximal inhibitory concentration

NOEL or NOEC: No Observed Effect Level or Concentration

ACGIH® - American Conference of Governmental Industrial Hygienists

•A1 - Confirmed human carcinogen

•A2 - Suspected human carcinogen

•A3 - Confirmed animal carcinogen with unknown relevance to humans

•A4 - Not classifiable as a human carcinoger

•A5 - Not suspected as a human carcinogen

IARC - International Agency for Research on Cancer •Group 1 - Carcinogenic to humans

•Group 2A - Probably carcinogenic to humans

•Group 2B - Possibly carcinogenic to humans

•Group 3 - Not classifiable as to carcinogenicity to humans •Group 4 - Probably not carcinogenic to humans

NTP - National Toxicology Program, U.S. Department of Health and Human Services
•Group K - Known to be Human Carcinogens

•Group R - Reasonably Anticipated to be Human Carcinogens

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Met. Corr.1: Corrosive to metals - Category 1

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

- · Sources Data arise from safety data sheets, reference works and literature.
- · \* Data compared to the previous version altered.