Tintometer[®] Group Water Testing



phone: +49 (0)231 94510-0 e-mail: sales@lovibond.com

phone: +44 1980 664800

e-mail: SDS@lovibond.uk

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name: Anionic / Polyamine Indicator P2/3
- · Catalog number: 56Z718198, 56L7181, 56L718130, 56L718165, 56U718130, 56U718165, SDT013
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation: Reagent for water analysis
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Tintometer GmbH Schleefstraße 8-12 44287 Dortmund Made in Germany www.lovibond.com

The Tintometer Limited Lovibond® House Sun Rise Way Amesbury Wiltshire SP4 7GR United Kingdom

· Informing department: e-mail: sds@lovibond.com Product Safety Department

· 1.4 Emergency telephone number:

+44 1235 239670 Languages: English

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Met. Corr.1 H290 May be corrosive to metals.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



Signal word Warning

(Contd. on page 2)

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

(Contd. of page 1)

· Hazard statements

H290 May be corrosive to metals.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P390 Absorb spillage to prevent material damage.

• 2.3 Other hazards At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

Determination of endocrine-disrupting properties

The product does not contain substances with endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: sulfuric acid solution

Dangerous components:		
CAS: 7664-93-9 EINECS: 231-639-5 Index No: 016-020-00-8 Reg.nr.: 01-2119458838-20-XXXX	sulphuric acid Met. Corr.1, H290; Skin Corr. 1A, H314 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 15 % Skin Irrit. 2; H315: 5 % ≤ C < 15 % Eye Dam. 1; H318: C ≥ 15 % Eye Irrit. 2; H319: 5 % ≤ C < 15 %	5–10%
CAS: 64-17-5 EINECS: 200-578-6 Index No: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	≤2.5%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information Instantly remove any clothing soiled by the product.
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- After skin contact

Instantly rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact Rinse opened eye for several minutes (at least 15 min) under running water. Then consult doctor.

After swallowing

Rinse out mouth and then drink 1-2 glasses of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed:

irritations

Drying-out effect resulting in rough and chapped skin.

after inhalation:

mucosal irritations, cough, shortness of breath

after swallowing:

sickness

diarrhoea

CNS disorders

· Danger Danger of system failure.

(Contd. on page 3)

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed: No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · 5.2 Special hazards arising from the substance or mixture

mixture with combustible ingredients

Formation of toxic gases is possible during heating or in case of fire.

Can be released in case of fire:

Sulphur oxides (SOx)

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Advice for emergency responders: Protective equipment: see section 8
- 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- · Advice on safe handling:

Ensure good ventilation/exhaustion at the workplace.

Keep ignition sources away - Do not smoke.

· Hygiene measures:

Avoid contact with the skin.

Avoid contact with the eyes.

Take off immediately all contaminated clothing.

Wash hands during breaks and at the end of the work.

Do not eat, drink or smoke when using this product.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and containers:

Store in cool location.

Keep only in original packaging.

Information about storage in one common storage facility:

Store away from metals.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Protect from heat and direct sunlight.

Protect from the effects of light.

Protect from humidity and keep away from water.

(Contd. on page 4)

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

· Recommended storage temperature: 20°C +/- 5°C

(Contd. of page 3)

Troopining and a storage temperature. 20 0 17 0 0

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with limit values that require monitoring at the workplace:		
CAS: 7664-93-9 sulphuric acid		
WEL (Great Britain)	Long-term value: 0.05* mg/m³ *mist: defined as thoracic fraction	
IOELV (European Union)	Long-term value: 0.05 mg/m³	
CAS: 64-17-5 ethanol		
WEL (Great Britain)	Long-term value: 1920 mg/m³, 1000 ppm	

· Regulatory information

WEL (Great Britain): EH40/2020

IOELV (European Únion): (EU) 2019/1831

Additional information: IOELV = Indicative Occupational Exposure Limit

·DNELs

Derived No Effect Level (DNEL)

Delived No Ellect Level (DNEE)			
CAS: 7664-93-9 sulphuric acid			
Inhalative DNEL 0.1 mg/m³ (Worker / acute / local effects)			
0.05 mg/m³ (Worker / acute / systemic effects)			
CAS: 64-17-5 ethanol			
Oral	DNEL	87 mg/kg (Consumer / long-term / systemic effects)	
Dermal	DNEL	343 mg/kg (Worker / long-term /systemic effects)	
		206 mg/kg (Consumer / long-term / systemic effects)	
Inhalative	DNEL	1900 mg/m³ (Worker / acute / local effects)	
		950 mg/m³ (Worker / long-term /systemic effects)	
		950 mg/m³ (Consumer / acute / local effects)	
		114 mg/m³ (Consumer / long-term / systemic effects)	
-	CAS: 64-1 Oral Dermal	Inhalative DNEL CAS: 64-17-5 eth Oral DNEL Dermal DNEL	Inhalative DNEL O.1 mg/m³ (Worker / acute / local effects) O.05 mg/m³ (Worker / acute / systemic effects) CAS: 64-17-5 ethanol Oral DNEL B7 mg/kg (Consumer / long-term / systemic effects) Dermal DNEL One DNEL One DNEL One DNEL One DNEL One One DNEL One One One One One One One One One One One One

Recommended monitoring procedures:

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and DIN EN 689.

· PNECs

Predicted No Effect Concentration (PNEC)

CAS: 7	CAS: 7664-93-9 sulphuric acid				
PNEC	8.8 mg/l (Sewage treatment plant)				
	0.00025 mg/l (Marine water)				
	0.0025 mg/l (Fresh water)				
PNEC	0.002 mg/kg (Marine sediment)				
	0.002 mg/kg (Fresh water sediment)				
CAS: 6	4-17-5 ethanol				
PNEC	PNEC 580 mg/l (Sewage treatment plant)				
	0.79 mg/l (Marine water)				
	2.75 mg/l (Aquatic intermittent release)				
	0.96 mg/l (Fresh water)				
PNEC	0.63 mg/kg (Soil)				
	3.6 mg/kg (Fresh water sediment)				

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls

· Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

(Contd. on page 5)

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

(Contd. of page 4)

Individual protection measures, such as personal protective equipment

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled.

- · Eye/face protection Safety glasses
- Hand protection

Protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Material of gloves

nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.11 mm

· Penetration time of glove material

Value for the permeation: Level = 1 (< 10 min)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Other skin protection (body protection): Protective work clothing.
- · Breathing equipment: Use breathing protection against the effects of fumes/dust/aerosol.
- · Recommended filter device for short term use: Combination filter A-P2
- · Environmental exposure controls Do not allow product to reach sewage system or water bodies.

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties • Physical state Fluid

Form: Solution
Colour: Yellow-brown
Odour: Like alcohol
Odour threshold: Not determined.

• Melting point/Freezing point:
• Boiling point or initial boiling point and boiling range Not determined.

Flammability mixture with combustible ingredients

• **Explosive properties:** Product is not explosive.

Lower and upper explosion limit

Lower:Not applicable.Upper:Not applicable.

• Flash point: > 60°C (Lit: 5%, CAS: 64-17-5 ethanol)

Auto-ignition temperature:
 Decomposition temperature:
 pH
 Kinematic viscosity
 Not determined.
 Strongly acidic
 Not determined.

Solubility

· Water: Fully miscible

Partition coefficient n-octanol/water (log value) Not applicable (mixture).

· Vapour pressure:

Not determined.

Density and/or relative density

Density at 20°C:

Relative density:

Relative gas density

Particle characteristics

1.1 g/cm³

Not determined.

Not determined.

Not applicable (liquid).

9.2 Other information

 \cdot Information with regard to physical hazard classes

Corrosive to metals
 May be corrosive to metals.

· Metals that are corroded by the substance or mixture Information on incompatible materials can be found in Sections 7 and

10.

Other safety characteristics

· Oxidising properties: none

Additional information

· Solids content: ≤ 0.1 %

Solvent content:

· Organic solvents: < 2.5 %

(Contd. on page 6)

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

(Contd. of page 5)

· **Water**: > 90 %

SECTION 10: Stability and reactivity

- · 10.1 Reactivity see section 10.3
- 10.2 Chemical stability Stable at ambient temperature (room temperature).
- 10.3 Possibility of hazardous reactions

Corrosive action on metals

Reacts with metals forming hydrogen (Danger of explosion in case of large amounts!)

Heating occurs when water is added

Reacts with reducing agents

Reacts with acids and alkali (lyes).

Reacts with ammonia (NH₃).

- · 10.4 Conditions to avoid Strong heating (decomposition)
- · 10.5 Incompatible materials:

metale

combustible substances

organic solvents

· 10.6 Hazardous decomposition products: see section 5

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:		
CAS: 7664-93-9 sulphuric acid		
Oral	LD50	2140 mg/kg (rat) (IUCLID)
Inhalative LC		510 mg/m³/2h (rat) IUCLID
CAS: 64-17-5 ethanol		nanol
Oral	LD50	10470 mg/kg (rat) OECD 401
Dermal	LD50	>20000 mg/kg (rabbit)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Information on components:

Skin irritation testing performed on 10% sulfuric acid showed slight to no irritation effects (GESTIS).

CAS 7664-93-9: chronic: dermatitis

CAS: 64-17-5 ethanol		
Irritation of skin	OECD 404	(rabbit: no irritation)
		(ECHA, registrant)
Irritation of eyes	OECD 405	(rabbit: irritation)

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Respiratory of skin sensitisation based on available data, the classification chiefla are not met.		
· Information on compor	ents:	
CAS: 64-17-5 ethanol		
Sensitisation OECD 406	(guinea pig: negative) (read across CAS 67-56-1)	

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · Information on components:

CAS: 64-17-5 ethanol

OECD 471 (negative) (Bacterial Reverse Mutation Test - Ames test)

(Salmonella typhimurium)

(Contd. on page 7)

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

(Contd. of page 6)

- STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

· Information on likely routes of exposure

The intake of sulfuric acid is mainly to be expected via the inhalative pathway in the form of aerosols. No studies on absorbability are available.

Generally, local reactions cause the main effects.

Following impact to the skin strong local effects are the main issue. There is no indication of absorption of relevant amounts of S. via the intact skin.

Absorbability via the gastrointestinal tract is assumed. However, no studies on the kinetics of uptake are available. [GESTIS] Under occupational conditions, the main uptake route for ethanol is through the respiratory tract. [GESTIS]

· Additional toxicological information:

Vapours and aerosols may be irritant to the mucous membranes and upper respiratory tract.

CAS: 7664-93-9 sulphuric acid

(source: GESTIS)

Main toxic effects

Acute: Irritation up to chemical burns to the mucous membranes and skin, danger of serious damage to the eyes and lungs Chronic: Irritation to the eyes and airways, erosion of the teeth, damage to the skin

Further Information:

Concentrated S. differs considerably from dilute Sulfuric acid with regard to chemical properties and effects. With increased dilution Sulfuric acid acts less aggressively.

- · 11.2 Information on other hazards
- Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- Other information

According to the information available to us, the chemical, physical and toxicological properties of the substances mentioned in Chapter 3 have not been thoroughly investigated.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:					
CAS: 7	CAS: 7664-93-9 sulphuric acid				
EC50	>100 mg/l/48h (Daphnia magna) (OECD 202) (ECHA)				
LC50	16–29 mg/l/96h (bluegill) (Merck)				
CAS: 6	CAS: 64-17-5 ethanol				
LC50	8140 mg/l/48h (gold orfe) (IUCLID)				
EC50	9268–14221 mg/l/48h (Daphnia magna) (IUCLID)				
NOEC	9.6 mg/l (Daphnia magna) (9d) (ECHA)				

· Bacterial toxicity:

sulphates toxic > 2.5 g/l

CAS: 64-17-5 ethanol

EC5 6500 mg/l (Pseudomonas putida) (16h)

Other information:

Toxic for fish:

Sulphates > 7 g/l

· 12.2 Persistence and degradability

CAS: 64-17-5 ethanol

OECD 301 E 94 % (readily biodegradable) (Modified OECD Screening Test)

· 12.3 Bioaccumulative potential

Pow = n-octanol/wasser partition coefficient

(Contd. on page 8)

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

log Pow < 1 = Does not accumulate in organisms.

(Contd. of page 7)

CAS: 64-17-5 ethanol

log Pow -0.32 (.)

- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects Avoid transfer into the environment.
- · Water hazard:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to disposers of hazardous waste.

- European waste catalogue
- 16 05 06* laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1760
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1760 CORROSIVE LIQUID, N.O.S. (SULPHURIC ACID) CORROSIVE LIQUID, N.O.S. (SULPHURIC ACID)

- · 14.3 Transport hazard class(es)
- · ADR



· Class 8 (C9) Corrosive substances. · Label 8

· IMDG, IATA



ClassLabel8 Corrosive substances.8

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Corrosive substances.

80

· Kemler Number:

· **EMS Number:** F-A,S-B

(Contd. on page 9)

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

(Contd. of page 8)

· 14.7 Maritime transport in bulk according	to IMC)
instruments		Ν

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· Transport category 2 · Tunnel restriction code E

· IMDG

Limited quantities (LQ)

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act UK
- · Regulated explosives precursors

The concentration of the substance is less than the stated mass percentage and should still be considered as reportable substance:

CAS: 7664-93-9 sulphuric acid 15%

- · Regulated poisons
- None of the ingredients is listed.
- · Reportable explosives precursors

None of the ingredients is listed.

- · Reportable poisons
- None of the ingredients is listed.
- · Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148:

All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see https://ec.europa.eu

explosives precursors - ANNEX I

CAS 7664-93-9: c < 15%

CAS: 7664-93-9 sulphuric acid

Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (PIC)

None of the ingredients is listed.

· Regulation (EC) No 1334/2000 setting up a Community regime for the control of exports of dual-use items and technology:

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

CAS: 7664-93-9 sulphuric acid

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries

in drug precursors

CAS: 7664-93-9 sulphuric acid 3

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer:

None of the ingredients is listed.

REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)

None of the ingredients is listed.

· LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV)

None of the ingredients is listed.

(Contd. on page 10)

3

Printing date 30.10.2023 Version number 2 (replaces version 1) Revision: 30.10.2023

Product name: Anionic / Polyamine Indicator P2/3

(Contd. of page 9)

Substances of very high concern (SVHC) according to REACH, Article 57

This product does not contain any substances of very high concern above the legal concentration limit of ≥ 0.1% (w / w).

Substances of very high concern (SVHC) according to UK REACH

This product does not contain any substances of very high concern above the legal concentration limit of ≥ 0.1% (w / w).

- · Directive 2012/18/EU (SEVESO III):
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- Information about limitation of use: Not required.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Training hints Provide adequate information, instruction and training for operators.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

Abbreviations and acronyms:

OECD: Organisation for Economic Co-operation and Development

STOT: specific target organ toxicity

SE: single exposure RE: repeated exposure

EC50: half maximal effective concentration

IC50: half maximal inhibitory concentration

NOEL or NOEC: No Observed Effect Level or Concentration

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of

Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Met. Corr.1: Corrosive to metals - Category 1

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

- · Sources Data arise from safety data sheets, reference works and literature.
- * Data compared to the previous version altered.

GB