

Lovibond® Colour Measurement Tintometer® Group



TLC 60 Lighting Cabinet

Colour Matching under the Perfect Light Source



- Render Colour More Accurately - Every Time
- You can Select from 6 Different Light Sources to Detect Any Potential Illuminant Metameric Failure
- Meet Major International Standards for Visual Colour Measurement including: ASTM D1729, ISO3664, DIN, ANSI and BSI
- Choice of Two Units Depending on your Sample Size

Artigo No: 403055

Render Colour More Accurately - Every Time

The accurate Quality Control of colour means the product should, as far as possible, look identical irrespective of the lighting conditions: whether inside, outside or under artificial retail lights. The colour of materials that might match perfectly under and International Standard Artificial Light might appear quite different to each other under a UV Light. By using a lighting cabinet, you can quickly and easily match colours under different light sources with a single unit.

Adhere to the International Standards of Light

The TLC range provides you with 6 of the most important, international light sources to detect any potential illuminant metamer failure:

Light Source	Light Simulation	Colour Temperature
F	Tungsten (Illuminant A)	2800
D65	International Standard Artificial Light	6500
TL84	Energy Efficient Store Lighting in Europe, Japan and China	4000
UV	Ultraviolet Light	λ 365
CW/F	Cool White Fluorescent (American Standard)	4150
TL83/U30	Warm White Fluorescent	3000

As such, the TLC series meets all the major international Standards for Visual Colour Measurement including:

- ASTM D1729, ISO3664, DIN, ANSI and BSI

Flexibility

The TLC series is ideal for use across multiple applications such as Textiles, Dyeing, Packaging, Leather, Inks, Knitwear, Plastics, Automotive and Ceramics; so one unit is all you need to measure multiple samples of incoming and outgoing goods.

Save Time, Energy and Efficiency

The cabinets are easy to operate with each light source having its own switch. No warming up time makes them quick, reliable and very highly energy efficient. Efficiency is further assured with their economic power consumption and low heat generation. There is also a timing meter to track optimum lamp replacement requirements.

TLC 60 Lighting Cabinet

The TLC series of Color Assessment Cabinets are suitable for all industries and applications where there is a need to maintain color consistency and quality. Since different light sources have different radiant energy, they display slightly different colours when reflected from a surface. So an operator comparing the color between the standard and the sample might be working in an alternative lighting environment to that being used by the client / recipient. To resolve this problem, it is best to always match the color under the same light source.

Configured Light Sources

- F, D65, TL84, UV, CWF, TL83/ U30

Dados Técnicos

Tela Sensível ao Toque Não

Dimensões 710 x 570 x 530 mm

Peso 38 kg

Texto do Escopo de Entrega

- Cabinet consisting of 5 component parts
- Assembly instructions
- Power supply
- Standard light sources
- Optional Accessory**
- Additional specialised light sources
- Replacement lamps

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
Fax: +49 (0)231/94510-30
sales@lovibond.com
www.lovibond.com
Germany

Tintometer China

Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.com
USA

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuhr Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@tintometer.com
www.lovibondwater.in
India

Tintometer AG

Hauptstraße 2
5212 Hausen AG
Tel.: +41 (0)56/4422829
Fax: +41 (0)56/4424121
info@tintometer.ch
www.tintometer.ch
Switzerland

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@tintometer.com.br
www.lovibond.com.br
Brazil

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain