

Lovibond® Water Testing

Tintometer® Group



PTV 6000 with Ethernet & Bluetooth; Laser

Next Generation of On-line Turbidity Measurement



- Smart Interface - Rethink the Controller
- Simplified and Streamlined Processes
- Innovative, Low Maintenance Design
- Unsurpassed Accuracy for low-level effluent measurement

Part Number: 6155624

Process Simplified - A New Approach

Details matter. The development of the PTV Series considered every aspect of process turbidity workflow - from installation and setup; daily measurement and control; routine procedures such as calibration, verification and maintenance; to data collection and management.

Smart User Interface - Rethink the Controller

We've replaced the need for a traditional controller with the familiar interface of a smart device. By utilizing a mobile device app, the user experience is enhanced by allowing quick and easy data viewing, calculation of statistics and access to operator instructions and useful tips.

Designed to Save

Save time, money and water by using the PTV system. These instruments are optimised for drinking water applications with unsurpassed low range accuracy (below 1 NTU). It has a variety of features that help users save.

Regulatory Compliant

The PTV Series has instruments that meet EPA and ISO regulatory requirements.

Fluidics Manager

The Fluidics Manager is an additional accessory that streamlines sample flowing into and out of the instrument. This eliminates the need to install and maintain separate devices to control sample entering and exiting the sensor.

Panel Mounting System

A Place for Everything. The Panel Mount is an additional accessory that aids in the installation of key instrument components and accessories.

Two Ways to Interface

Touchscreen Interface - All PTV Series instruments are supplied with an integrated touchscreen. All measurement settings and routine functions such as calibration can be managed directly with the touchscreen without the need for additional devices.

AquaLXP™ Interface - The AquaLXP™ app is an enhanced version of the touchscreen. In addition to being able to perform all of the functions as the touchscreen, users have access to animated instructions of all procedures, advanced data analysis and statistics tools, complete maintenance and repair logs as well as the comfort of using a familiar device.

Wet Standards - for Calibration & Verification

T-CAL Turbidity Standards from Lovibond® Tintometer® are primary standards that are US EPA and ISO compliant.

When you combine our T-CAL Turbidity Standards and our T-CALplus™ packaging, turbidity standards have never been easier to use.

Industry

Municipalities

PTV 6000 with Ethernet & Bluetooth; Laser

Turbidity is the key measurement parameter for determining drinking water quality.

To develop this instrument, Lovibond® Tintometer® assembled a team of globally recognized turbidity experts. We tasked them with creating a new process instrument that addresses all of the issues customers struggle with while using their current turbidity systems. These advancements, along with the addition of state-of-the-art communications and user interface make the PTV 1000 and PTV 2000 the next generation of process turbidimeters.

Technical Data

| | |
|--|--|
| Optics | Laser |
| Accuracy | ± 2 % of reading from 0 to 10 NTU ± 4 % of reading between 10 to 100 NTU |
| Stray Light | smaller 0.005 / 5 mNTU |
| Displayed Resolution | up to 0.0001 NTU (range dependent) or 5 digits displayed |
| Repeatability / Precision | better than 1% at 1 NTU |
| Initial Response | 10 % change: 15 seconds @ max flow |
| Step Response | (T-90), less than 240 seconds at 200 ml/min. at 1 NTU |
| Signal Averaging | User Selectable: 1, 3, 6, 10, 30, 60, and 90 seconds, defaulted to 30 seconds |
| Sample Temperature | 0 - 50 °C max sample temperature: 70 °C |
| Sample Flow | 30 to 500 ml/min, optimal flow: 50 to 80 ml/min |
| Sample Inlet Connection | 1/4-inch NPT female, 1/4-inch compression fitting tubing (included) |
| Sample Outlet (Drain) Connection | 3/8-inch NPT female, 3/8-inch hose barb tubing (included) |
| Power Requirements | 90 to 264 VAC, 50/60 Hz. Auto Select |
| Sample Inlet Tubing | 1/4-inch OD or 6 mm OD |
| Sample Outlet Tubing | 3/8-inch OD or 9 mm OD |
| Turbidimeter Body Drain | Quick connect with integrated check valve |
| Calibration | One Point Calibration at 5.0 or 20 NTU with any regulatory approved formazin |
| Analog Output: Measurement Module | 1 selectable 0 - 20 mA or 4 - 20 mA; output span programmable over any portion of the measurement range |
| Analog Output: Junction Box | 1 selectable 0 - 20 mA or 4 - 20 mA; output span programmable over any portion of the measurement range |
| Alarms | Three set-point alarms, each equipped with an SPDT relay with unpowered contacts rated 5 A resistive load at 230 V, AC |
| Enclosure Type: Junction Box | Fiber reinforced polyester |
| Enclosure Rating: Junction Box | IP 66 |
| Safety | Listed by TÜV Rheinland to UL 61010A-1: Certified by TÜV Rheinland to CSAC22.2 No. 1010.1: CE Certified by TÜV Rheinland to EN 61010-1 |
| Immunity | CE certified by TÜV Rheinland to EN 61326 (Industrial Levels) |
| Emissions | Class A: EN 61326, CISPR 11, FCC Part 15, Canadian Interference-Causing Equipment Regulation ICES-003 |
| Mounting Hardware | Turbidimeter Sensor - Slotted Mounting Bracket that can be affixed to any vertical surface or panel (Optional). Junction Box - Direct mounting to any vertical surface or panel (Optional) |
| Method of Verification | Wet Standards or dry verification device |
| Limit of Determination | 0.0001 NTU |
| Limit of Detection | 0.001 NTU |
| Flow Indicator | no |
| Portability | Process |
| Environmental Conditions | 5 - 50 °C, rel. humidity 5 - 95 % (Non-condensing) |

| | |
|-------------------------|--------------------------|
| Protection Class | IP 65 |
| Compliance | EPA |
| Dimensions | 158.5 x 340.4 x 334.5 mm |
| Weight | 5 kg |

Accessories

| Title | Part Number |
|---|-------------|
| Kit, Bubble Trap Cover and O-ring, for PTV 6000 | 19806-048 |
| Assembly, Float | 19806-054 |
| Assembly, Fluidics Manifold | 19806-056 |
| Constant Head Height Regulator | 19806-058 |
| Kit, Fittings & Tubing | 19806-059 |
| T-CALplus Calibration Tube Assembly (Blue Tube)- | 19806-062 |
| Cleaning Tube Assembly (Black Tube) | 19806-072 |
| Kit, Bubble trap cover Replacement (comes with O-ring) | 19806-077 |
| Kit, Knob for bubble trap | 19806-079 |
| Kit, Drain fitting | 19806-080 |
| Kit, Drain cover | 19806-081 |
| Kit, Flow body assembly, with Flow Meter | 19806-083 |
| Kit, Flow body assembly, without Flow Meter | 19806-084 |
| Kit, Illuminator Lens Sub Assembly | 19806-085 |
| Kit, Installation Connectors | 19806-086 |
| Rotometer, 25 to 100 mL/min | 19806-087 |
| Panel, Instrument and Sample Management | 19806-088 |
| Brass mounting cup assembly | 19806-106 |
| Dry Verification STD, High Range (> 10 NTU) | 19806-110 |
| Dry Verification STD, Low Range (< 10 NTU) | 19806-111 |
| Mounting Cleat with Interlock, for PTV 6000 | 19806-119 |
| Fuse, 1.6A, 250VAC | 19806-206 |
| Illuminator O-ring | 19806-407 |
| O-ring, for Beam Dump | 19806-416 |
| Tubing, 1/4" OD, black, Polyethylene | 19806-429 |
| O-ring, Rear Drain cover | 19806-434 |
| Fitting, Quick Connect, Male | 19806-436 |
| Lanyard Strap | 19806-448 |
| Fitting, Quick Connect, Female | 19806-449 |
| Plug for Conduit holes | 19806-487 |
| Valve; 1/4" Tubing Quick Connect | 19806-494 |
| Tablet Wall Mount | 19806-521 |
| Strain Relief, 3/8" NPT | 19806-527 |
| Tubing, 3/8" ID x 1/2" OD x 1/16" Wall, Clear PVC | 19806-531 |
| Seal, Bubble trap cover, -241 - | 19806-554 |
| Insert, Measurement Module Holder, Instrument Panel | 19806-570 |
| Measurement Module, PTV 6000 | 19806-706 |
| Measurement Module, PTV 6000 with, with Bluetooth® | 19806-707 |
| Kit, Beam Dump Guard / Interlock, Fitting & O-rings, for PTV 6000 | 19806-716 |
| Pad, Application, Microfiber, w/pocket | 19806-803 |
| Rinse bottle, 500 ml | 420056 |
| T-CALplus® -Standard, 0.30 NTU, Standard for Verification | 48010035 |
| T-CALplus® -Standard, 1.00 NTU, Standard for Verification | 48010135 |
| T-CALplus® -Standard, 5.00 NTU, Standard for Calibration | 48010235 |
| T-CALplus® -Standard, 20 NTU, Standard for Calibration | 48010335 |
| T-CAL® -Standard, 0,30 NTU, 500 ml | 48011050 |
| T-CAL® -Standard, 1,00 NTU, 500 ml | 48011150 |
| T-CAL® -Standard, 5,00 NTU, 500 ml | 48012250 |
| T-CAL® -Standard, 20,00 NTU, 500 ml | 48012350 |
| Cleaning Solution | 54010435 |
| Detergent Solution | 54011010 |
| Scale Remover | 54013003 |

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebu Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain