

# Lovibond® Water Testing

## Tintometer® Group



## Water Treatment Engineers Test Kit (Photometer)

Test Kit for professionals for water treatment with photometric focus



You need safe, fast and reliable test results? This Kit allows you to test your water system in your daily routine with visual methods, electrochemical instruments and additionally with an MD600 photometer for advanced water analysis. This gives you the full overview and enables you to make the appropriate decisions on treatment programs.

Includes the following parameters: Conductivity, pH, glycol, aluminum, bromine, chlorine, copper, iron, molybdate and phosphate.

- Mobile laboratory for water treatment monitoring
- Accurate & repeatable results for all types of industrial water systems
- Including photometer MD600 for professional photometric tests
- Ensure system performance & operating costs

Referencia No: 56K701400

### Industria

Energía | Gas y petróleo | Industria alimentaria | Industria farmacéutica | Industria naval | Industria química | Municipios | ONG | Otras industrias | Piscina privada | Piscina pública | Servicios para piscinas

### Aplicaciones

Agua de caldera | Agua de refrigeración | Control de aguas de piscina | Control de desinfección | Galvanizado | Otros | Tratamiento de aguas de aporte | Tratamiento de aguas potables | Tratamiento de aguas residuales

### Water Treatment Engineers Test Kit (Photometer)

The complete equipment for monitoring of closed circuits, evaporative cooling systems & boiler systems as routine tasks.

Ideal for prevention of most common problems and risks like corrosion, scale and biofouling or increased biological activity. The kit additionally contains an MD600 Photometer for professional photometric water sample analysis.

## Rango de medición

Test Name	Rango de medición	Método químico
Alcalinidad (P, M, OH)	50 - 2400 mg/L CaCO <sub>3</sub>	
Aluminio T	0.01 - 0.3 mg/L Al	Eriocromcianina R
Bromo T	0.05 - 13 mg/L Br <sub>2</sub>	DPD
Chloride	20 - 12000 mg/L Cl <sup>-</sup>	
Cloro T	0.01 - 6.0 mg/L Cl <sub>2</sub> <sup>a)</sup>	DPD
Cobre T	0.05 - 5 mg/L Cu <sup>a)</sup>	Biquinolina
Conductivity	0 - 20 mS/cm	
Dureza, total	5 - 600 mg/L CaCO <sub>3</sub>	
Dureza (Sí/No)	8 - 20 mg/L CaCO <sub>3</sub>	
Fosfato HR T	0.33 - 26 mg/L P	Vanadomolibdato
Fosfonato	0 - 20 mg/L HEDP	
Glicol	% PEG/MEG	
Hardness Calcium	5 - 600 mg/L CaCO <sub>3</sub>	
Hierro HR L	0.1 - 10 mg/L Fe	Tioglicolato
Hierro LR L (A)	0.03 - 2 mg/L Fe	Ferrocina / Tioglicolato
Hydrogen Peroxide	15 - 500 mg/L H <sub>2</sub> O <sub>2</sub>	
Molibdato T	1 - 50 mg/L MoO <sub>4</sub>	Tioglicolato
Nitrito	10 - 2000 mg/L NaNO <sub>2</sub>	
pH	0 - 14	
Sulfito	25 - 150 mg/L Na <sub>2</sub> SO <sub>3</sub>	
Tanino	50 - 300 mg/L Tannin	

## Volumen de suministroo

- Plastic case
- SD40 Multi Pocket Tester
- MD610 Photometer
- 6 Cuvettes 24 mm round with lids & sealing rings
- DPD No.1 tablets BT
- DPD No.3 tablets
- Glycine tablets
- Nitrite tablets bottle
- Aluminium No.1 tablets
- Aluminium No.2 tablets
- Copper No.1 Test tablets
- Copper No.2 Test tablets
- Molybdate No.1 tablets
- Molybdate No.2 tablets
- Phosphate HR P1 tablets
- Phosphate HR P2 tablets
- Hardness Yes/No tablets
- Stirring rod and powder spoon
- pH Buffer 4 solution
- pH Buffer 7 solution
- pH Buffer 10 solution
- Chloride LR Titrant CC2
- Chloride HR Titrant BC2
- Tannin Indicator TN1
- Tannin Titrant TN2
- Acetic acid 20%
- Nitrite Titrant N2
- Phosphonate Titrant P5
- Peroxyacetic acid Buffer HP1
- Phosphonate Indicator P4L
- Nitrite Indicator N1
- Hydrogen Peroxide HR Titrant HP2
- Hydrogen Peroxide HR Titrant HP3
- Iron Reagent FE8
- Phosphonate pH Adjuster P3
- Chloride Indicator CC1
- Calcium Hardness Indicator CH1P
- Calcium Hardness Buffer CH2
- Phosphonate Neutraliser P1/2
- Sulphite Indicator S1
- Sulphite Titrant S2
- Alkalinity 4.5 Indicator TA4
- Alkalinity LR Titrant TA3
- Alkalinity HR Titrant PA2/TA2
- Alkalinity OH Reagent PA3
- Acidity/Alkalinity P Indicator PA1
- Hardness Total Buffer TH2
- Hardness Total Indicator TH1P
- Hardness LR Titrant TH3
- Hardness HR Titrant TH4
- 1413uS Standard Conductivity Solution
- Iron Reagent FE6

## Accesorios

Título	Referencia No
ValidCheck cloro 1,5 mg/l	48105510
Jeringuilla, plástico, 20 mL	56A006501
Recipiente de valoración con tapa, plástico, 60 mL	56A006701
Jeringuilla de plástico, 5 mL	56A008501
Jeringuilla de plástico 1 ml	56A013501
Tubo de ensayo 5/10 mL + tapa	56A600401
Refractómetro glicol	56M000401

---

### Tintometer GmbH

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Alemania

### The Tintometer Limited

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
Fax: +44 (0)1980 625412  
sales@lovibond.uk  
www.lovibond.com  
Reino Unido

### Tintometer China

9F, SOHO II C.  
No.9 Guanghualu,  
Chaoyang District,  
Beijing, 100020  
Customer Care China Tel.: 4009021628  
Tel.: +86 10 85251111 Ext. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

### Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malasia

### Tintometer Brazil

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brasil

### Tintometer Inc.

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
Estados Unidos de América

### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

### Tintometer Spain

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
España