

Lovibond® Water Testing

Tintometer® Group



Water Treatment Engineers Test Kit (advanced)

Advanced test equipment for water treatment professionals



- All instruments & reagents for daily routine
- Including advanced photometer MD640 for additional parameters
- Early prevention & detection of risks
- Ensure system performance & operating costs

Referencia No: 56K701500

Water treatment engineers are engaged daily in the control of water quality in closed circuits, evaporative cooling systems and boiler systems. They need reliable equipment and accurate results to rely on. Both have an important impact on decisions on treatment programs and optimal system performance

This Advanced Engineers Kit contains all you need to protect the life of the plant and operating costs. It allows early detection of corrosion, scale and biofouling and the investigation of increased biological activity.

Includes the following parameters: Conductivity, pH, glycol, aluminum, bromine, chlorine, copper, iron, molybdate, phosphate and alkalinity (M, P, OH).

Industria

Energía | Gas y petróleo | Industria alimentaria | Industria farmacéutica | Industria naval | Industria química | Municipios | ONG | Otras industrias | Piscina privada | Piscina pública | Servicios para piscinas

Aplicaciones

Agua de caldera | Agua de refrigeración | Control de aguas de piscina | Control de desinfección | Galvanizado | Others | Tratamiento de aguas de aporte | Tratamiento de aguas potables | Tratamiento de aguas residuales

Water Treatment Engineers Test Kit (advanced)

This kit contains pocket meters, checkit comparator, drop tests and MD640 photometer for advanced testing an extended range of control parameters.

Take the complete equipment for direct on-site analysis in practical case in one hand.

Advances analysis of all types of industrial water with visual, electrochemical and photometric methods.

Rango de medición

Test Name	Rango de medición	Método químico
Alcalinidad (P, M, OH)	50 - 2400 mg/L CaCO ₃	
Aluminio T	0.01 - 0.3 mg/L Al	Eriocromcianina R
Bromo T	0.05 - 13 mg/L Br ₂	DPD
Chloride	20 - 12000 mg/L Cl ⁻	
Cloro T	0.01 - 6.0 mg/L Cl ₂ ^{a)}	DPD
Cobre T	0.05 - 5 mg/L Cu ^{a)}	Biquinolina
Conductivity	0 - 200 mS/cm	
Dureza, total	5 - 600 mg/L CaCO ₃	
Dureza (Sí/No)	8 - 20 mg/L CaCO ₃	
Fosfato HR T	0.33 - 26 mg/L P	Vanadomolibdato
Fosfonato	0 - 20 mg/L HEDP	
Glicol	% PEG/MEG	
Hardness Calcium	5 - 600 mg/L CaCO ₃	
Hierro HR L	0.1 - 10 mg/L Fe	Tioglicolato
Hierro LR L (A)	0.03 - 2 mg/L Fe	Ferrocina / Tioglicolato
Hydrogen Peroxide	15 - 500 mg/L H ₂ O ₂	
Molibdato T	1 - 50 mg/L MoO ₄	Tioglicolato
Nitrito	10 - 2000 mg/L NaNO ₂	
pH	-2 - 16	
PTSA	10 - 400 ppb	Fluorescencia
Sulfito	25 - 150 mg/L Na ₂ SO ₃	
Tanino	50 - 300 mg/L Tannin	

Volumen de suministro

- Plastic case
- 6 Cuvettes 24 mm round with lids & sealing rings
- SD 335 Multi
- MD640 Photometer
- Brush, 11 cm length
- DPD No.1 tablets BT
- DPD No.3 tablets
- Glycine tablets
- DPD Nitrite tablets bottle
- Aluminium No.1 tablets
- Aluminium No.2 tablets
- Copper No.1 Test tablets
- Copper No.2 Test tablets
- Molybdate No.1 tablets
- Molybdate No.2 tablets
- Phosphate H.R.P1 tablets
- Phosphate H.R.P2 tablets
- Copper/Zinc L.R.Test Tablets
- Hardness Yes/No tablets
- pH Buffer 4 solution
- pH Buffer 7 solution
- pH Buffer 10 solution
- 1413uS Standard Conductivity Solution
- Iron Reagent FE6
- Iron Reagent FE5
- Alkalinity 4.5 Indicator TA4
- Alkalinity LR Titrant TA3
- Alkalinity HR Titrant PA2/TA2
- Alkalinity OH Reagent
- Hardness Total Buffer TH2
- Hardness Total Indicator TH1P
- Hardness LR Titrant TH3
- Hardness HR Titrant TH4
- Chloride LR Titrant CC2
- Chloride HR Titrant BC2
- Tannin Indicator TN1
- Tannin Titrant TN2
- Acetic acid 20%
- Nitrite Titrant N2
- Phosphonate Titrant P5
- Hydrogen Peroxide Buffer HP1
- Phosphonate Indicator P4L
- Nitrite Indicator N1
- Hydrogen Peroxide HR Titrant HP2
- Iron Reagent FE8
- Phosphonate pH Adjuster P3
- Chloride Indicator CC1
- Calcium Hardness Indicator CH1P
- Calcium Hardness Buffer CH2
- Phosphonate Neutraliser P1/2
- Sulphite Indicator S1
- Sulphite Indicator S2

Accesorios

Título	Referencia No
LC 12 para SD 320 / SD 325 Con, hasta 200 mS/cm	19805040
ValidCheck cloro 1,5 mg/l	48105510
Jeringuilla, plástico, 20 mL	56A006501
Recipiente de valoración con tapa, plástico, 60 mL	56A006701
Jeringuilla de plástico, 5 mL	56A008501
Jeringuilla de plástico 1 ml	56A013501
Tubo de ensayo 5/10 mL + tapa	56A600401
Refractómetro glicol	56M000401
SD 335 Multi (instrumento básico)	724830

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Alemania

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
Reino Unido

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malasia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brasil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Estados Unidos de América

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
España