

Lovibond® Water Testing Tintometer® Group



Boiler Water Test Kit

For daily expert control of water in boiler systems



This Test Kit has been designed to include the key parameters which enable the monitoring of samples in these water systems ensuring optimum operating conditions are maintained.

Provides accuracy and speed, utilising drop test and comparator reagents together with electronic meters for the most efficient monitoring of water samples to ensure correct water conditions.

This involves testing:

- Boiler water
- Raw make up water
- Softened make up water (requires ZERO hardness levels)
- Condensate returns
- Feedwater (combination of above waters in varying quantities)

Any failure to maintain the correct levels and dosing of the chemical treatments can lead to:

- Corrosion of the system (leaks)
- Formation of scale (blocked pipes)

These can lead to unstable water conditions with potential negative consequences to the life of the plant and operating costs.

- For maintaining & management of boiler systems
- Developed specifically for water engineers & treatment professionals
- Includes equipment for testing the key parameters
- Supports you ensuring optimum operating conditions

N. ordine: 56K701170

Industria

Altre industrie | Navigazione

Applicazione

Acqua di caldaia | Acqua di raffreddamento | Others

Boiler Water Test Kit

Re-circulating cooling water requires carefully chosen chemical treatments. This helps to minimise microbiological contamination, scaling of critical parts such as heat exchangers and to prevent corrosion.

To be most effective, treatments must be maintained within specific control parameters, as excess inhibitor can have as detrimental an affect as too little.

Campo di misura

Test Name	Campo di misura
Alkalinity (P, M, OH)	50 - 2400 mg/L CaCO ₃
Chloride	20 - 12000 mg/L Cl ⁻
Conductività	0 - 20 mS/cm
Durezza (Si/No)	8 - 20 mg/L CaCO ₃
Durezza totale	5 - 600 mg/L CaCO ₃
pH	0 - 14
Sulphite	25 - 150 mg/L Na ₂ SO ₃
Tannin	50 - 300 mg/L Tannin

Fornitura

- Plastic case
- SD40 Multi Pocket Tester
- Checkit Comparator
- 0 - 80 mg/L Phosphate HR Checkit Disc
- 2 plastic vials 10mL with lid
- Phosphate HR Comp. Tablets
- Hardness Yes/No Tablets
- pH Buffer 4
- pH Buffer 7
- pH Buffer 10
- 1413uS Standard Conductivity Solution
- Alkalinity 4.5 Indicator TA4
- Alkalinity LR Titrant TA3
- Alkalinity HR Titrant PA2/TA2
- Acidity / Alkalinity P Indicator PA1
- Alkalinity OH Reagent
- Hardness Total Buffer TH2
- Hardness LR Titrant TH3
- Hardness HR Titrant TH4
- Chloride Indicator CC1
- Chloride LR Titrant CC2
- Chloride HR Titrant BC2
- Sulphite Indicator S2
- Tannin Indicator TN1
- Tannin Titrant TN2
- Acetic acid 20%
- Hardness Total Indicator TH1P
- Sulphite Indicator S1
- Syringe plastic, 20 mL
- 2 Titration jars with cap, plastic, 60 mL
- Syringe filter holder, 25mm
- Filter circles GF/C, 25mm
- Instruction manual

Accessori

Titolo	N. ordine
CHECKIT® Comparator	145000
Siringa, plastica, 20 mL	56A006501
Vaso di titolazione con coperchio, plastica, 60 mL	56A006701
Siringa di plastica, 5 mL	56A008501
Filtro Gf/C, 25 mm	56A019950
SD40 Multi	720040

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
Regno Unito

Tintometer China

Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
Cina

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malesia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brasile

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Stati Uniti d'America

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spagna