

Lovibond® Water Testing

Tintometer® Group



THPS Test Kit

For monitoring the broadband biocide THPS



- Specially for cooling water & other industrial applications
- Effective against Sulphate Reducing Bacteria (SRB)
- Drop tests for up to 100 tests
- Easy to handle

N. ordine: 56K701210

Versatile application

THPS stands for Tetra Hydroxymethyl Phosphonium Sulphate. It is commonly regarded as an environmentally friendly biocide that is readily degradable and has low volatility. As a broad-spectrum biocide, it is effective against the most common types of bacteria that cause problems in cooling water, especially Sulphate Reducing Bacteria (SRB). THPS is also used for the control of Legionella. It inhibits the growth of algae, bacteria, yeasts and fungi in a wide range of industrial applications.

Keeping the dosage under control

With this Test Kit you can control the THPS concentration anytime and anywhere. Our Kits are designed for mobile use directly on site. This way, you quickly have certainty about the correct dosage, because misdosing can also cause damage to the water system and the material. This will save both time and money at the same time. Our Test Kits also provide compliance with the applicable regulations.

Industria

Altre industrie

Applicazione

Acqua di raffreddamento | Controllo disinfettante

THPS Test Kit

Microorganisms and bacteria are among the main causes of problems for cooling water and other industrial water. In the worst case, legionella can form. THPS is one of the most commonly used non-oxidising biocides to combat these problems.

Its effectiveness also depends on the correct dosage. With this Test Kit, you can quickly and easily monitor the use of THPS anywhere at any time.

Campo di misura

Test Name	Campo di misura
THPS	0 - 100 ppm

Fornitura

- Plastic case
- THPS Reagent 1
- THPS Reagent 2
- THPS Reagent 3
- Syringe plastic, 20 mL
- 2 Titration jars with cap, plastic, 60 mL
- Instruction manual

Accessori

Titolo	N. ordine
Siringa, plastica, 20 mL	56A006501
Vaso di titolazione con coperchio, plastica, 60 mL	56A006701
Siringa di plastica 10 ml	56A008601
Titration Burette, 1 mL	56A011101
Syringe Micro Burette	56A011201
Filtro Gf/C, 25 mm	56A019950

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germania

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
Regno Unito

Tintometer China

Room 1001, China Life Tower
16 Chaoyangmenwai Avenue,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 App. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
Cina

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebu Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malesia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brasile

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
Stati Uniti d'America

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spagna