

# Lovibond® Water Testing

## Tintometer® Group



### R2A/R2A Dipslide, Aerobic Bacteria, Dual Sided, 10 pack

With single agar for the determination of the total count



Guidelines to advise on the correct practices to control legionella bacteria in water systems exist worldwide. Suppressing bacteria levels does substantially reduce the possibility of an outbreak of this often fatal disease. Guidelines recommend introducing a monitoring and control program. This program includes the testing of cooling tower waters with dipslides on a regular basis. A full range of dipslides is available for semiquantitative determination of aerobic and anaerobic bacteria populations in industrial and recreational waters. Dipslide accuracy is limited due to the small sample size, but if used correctly and incubated at a constant temperature using the Lovibond® dipslide incubator, they are excellent for trend analysis and can give an early indication of bacteria proliferation.

- Determine aerobic and anaerobic bacteria levels
- Early indication of bacteria proliferation
- Results in 48 hours
- Inexpensive

Part Number: 56B011110

#### Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Oil and Gas | Pharmaceutical Industry | Power and Energy

#### R2A/R2A Dipslide, Aerobic Bacteria, Dual Sided, 10 pack

You need a low detection limit for the determination of the total count? Then this dipslide with single agar and R2A agar including TTC-additive is the right one for you: It has a lower detection limit than other dipslides because it counts from  $10^2$ . This Dipslide is compliant with the standards HTM 01-05, HTM 01-06 and Marine Conventions MLC, 2006 & ILO178.

#### Accessories

Title	Part Number
Dipslide Comparator - App	
DI10 Dipslide Incubator, 12 test Capacity	56B000701