

Lovibond® Water Testing Tintometer® Group



SD10 pH



- Transparent lid for easy maintenance and storage
- Ideal lid design for a stable stand
- Display colours & symbols for easy use
- New multi-parameter models for individual measurement requirements

货号: 720010

行业

NGO | 公共泳池 | 其他行业 | 家庭泳池 | 市政 | 海洋工业

应用

冷却水 | 污水处理 | 泳池水质控制 | 锅炉水 | 饮用水处理

SD10 pH

With its waterproof housing, the Pocket Tester is ideal for regular checks in industrial plants or swimming pools.

Plus, the transparent lid not only provides a secure stand for the Pocket Tester in daily use, but also makes it easier to maintain the electrodes. A three-colour LED lighting system - blue, green and red - and new display icons make the tester easy to use and intuitive to operate. The use of energy saving LEDs and 4 x AAA batteries greatly extends the life of the new Pocket Tester range to up to 2000 hours.

With the included lanyard, each SD Series tester can be worn comfortably around the neck or attached to a pocket, waistband or belt with the clip on the head of the tester, allowing it to be taken anywhere without tiring the hands.

测量范围

Test Name	测量范围
pH	0 - 14
pH (mV)	-1000 - 1000
Temperature	0 - 50 °C

Technical Data

精度	pH: ± 0.01 (± 1 digit) pH (mV): ± 0.2 % FS Temperature: ± 0.5 °C
显示	3 coloured backlit LCD (blue: measurement, green: calibration, red: alarm)
Auto – OFF	是
电源	4个Micro电池 (AAA)
电池寿命	> 2000 h
便携性	手提
解析度	pH: 0.01 ; pH (mV): 1
Resolution Temperature	0.1 °C
Calibration Points	1-3
Buffer Auto Recognition	USA: 1.68 / 4.00 / 7.00 / 10.01 / 12.45 pH NIST: 1.68 / 4.01 / 6.86 / 9.81 / 12.45 pH
Calibration Indicator	是
Stability Indicator	是
Auto-Hold Function	是
Alarm Limits	是
一致性	CE
尺寸	40 x 40 x 180 mm
带包装的重量	268 g

标准配置文本

- Meter in a robust plastic case with hanger
- 4 batteries
- Lanyard
- pH 4, 7, 10 buffer tablets (1 Strip of 10 tablets each)
- 3 M KCl Storage Solution for pH/ORP
- Instruction manual
- Warranty declaration
- Certificate of Compliance

标题

货号

pH 缓冲溶液 4.01 (25 °C) 红, 1 升, 可回溯至 N.I.S.T	721252
pH-缓冲溶液 7.00 (25 °C) 黄, 1 升, 可回溯至 N.I.S.T.	721254
pH-缓冲溶液 10.01 (25 °C) 蓝, 1 升, 可回溯至 N.I.S.T	721256
用于pH / ORP的3 M KCl存储溶液, 25毫升	726402
用于pH / ORP的3 M KCl存储溶液, 100毫升	726404

辅料

标题	货号
微电池 (AAA), 4 件套	1950026
量杯, 100 ml	384801
软化水	461275
缓冲平板电脑 pH 10	515600BT
缓冲平板电脑 pH 10	515601BT
缓冲平板电脑 pH 7	515610BT
缓冲平板电脑 pH 7	515611BT
缓冲平板电脑 pH 4	515620BT
缓冲平板电脑 pH 4	515621BT
用于 SD10 pH 的替换电极	720015
pH 缓冲溶液 4.01 (25 °C) 红, 90 ml 可回溯至 N.I.S.T	721247
pH-缓冲溶液 7.00 (25 °C) 黄, 90 ml 可回溯至 N.I.S.T.	721248
pH-缓冲溶液 10.01 (25 °C) 蓝, 90 ml 可回溯至 N.I.S.T.	721249
pH-缓冲溶液套件 pH 4, pH 7, pH 10 (25 °C), 90 ml	721250

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
德国

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
Fax: +44 (0)1980 625412
sales@lovibond.uk
www.lovibond.com
英国

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
中国

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
马来西亚

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
巴西

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
美国

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
印度

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
西班牙